



US00D461449S

(12) **United States Design Patent**
Kuroda et al.

(10) **Patent No.:** **US D461,449 S**

(45) **Date of Patent:** **** Aug. 13, 2002**

(54) **CONNECTOR FOR PRINTED CIRCUIT
BOARDS**

(75) Inventors: **Keiji Kuroda**, Amagasaki; **Daichi
Miyamoto**, Izumiotsu, both of (JP)

(73) Assignee: **J.S.T. Mfg., Ltd.**, Osaka (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/141,461**

(22) Filed: **May 8, 2001**

(30) **Foreign Application Priority Data**

Nov. 16, 2000 (JP) 2000-032834

(51) **LOC (7) Cl.** **13-03**

(52) **U.S. Cl.** **D13/133**

(58) **Field of Search** D13/133; 439/79,
439/83, 188, 871

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,767,361	A	*	8/1988	Hoshino et al.	439/596
5,055,058	A	*	10/1991	Nagasaka et al.	439/188
6,086,419	A	*	7/2000	Marpoe, Jr.	439/595
6,164,995	A	*	12/2000	Peloza	439/188
6,193,533	B1	*	2/2001	De Win et al.	439/188
6,261,131	B1	*	7/2001	Kuroda et al.	439/732
6,280,206	B1	*	8/2001	Kuroda et al.	439/83
D452,477	S	*	12/2001	Hiramoto et al.	D13/133

* cited by examiner

Primary Examiner—Joel Sincavage

(74) *Attorney, Agent, or Firm*—Antonelli, Terry, Stout & Kraus, LLP

(57) **CLAIM**

The ornamental design for a connector for printed circuit boards, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view;
FIG. 2 is a front elevation;
FIG. 3 is a bottom plan view;
FIG. 4 is a rear elevation;
FIG. 5 is a left-side elevation;
FIG. 6 is a right-side elevation;
FIG. 7 is a frontal perspective view of the connector; and,
FIG. 8 is a perspective view of contacts fixed therein.

The claimed design is directed to the appearance of the connector in its assembled state as shown in FIGS. 1–7. The contacts are shown separately in FIG. 8 for the purpose of clarifying design aspects of the assembled connector that are not be apparent from the other views.

The present design is characterized in that, in addition to parallel grooves formed in side faces, the connector has two contacts fixed therein wherein one of the contacts has a shorter body and a shorter arm as compared with the other contact, and in that the ends of the arms are bent in opposite directions, disposed remote from each other and exposed in the opposite side faces of the connector.

1 Claim, 3 Drawing Sheets




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8

