



US00D464521S

(12) **United States Design Patent**
Graves

(10) **Patent No.:** **US D464,521 S**

(45) **Date of Patent:** **** Oct. 22, 2002**

(54) **TAILBONE CUSHION PAD**

(76) **Inventor:** **Noble L Graves, 5401 Chimney Rock,
Apt 1019, Houston, TX (US) 77081**

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/142,494**

(22) **Filed:** **May 25, 2001**

(51) **LOC (7) Cl.** **06-09**

(52) **U.S. Cl.** **D6/601**

(58) **Field of Search** D6/595, 596, 597,
D6/599, 601, 602, 603, 604, 605, 606,
608; D2/720, 728, 823, 860, 861; D8/403;
D24/184, 189, 192; 2/114, 914, 915, 466,
467, 267; 5/417, 418, 419, 420, 485, 486,
495, 499, 630, 631, 632, 633, 636, 637,
638, 639, 640, 641, 644, 645, 646, 648,
650, 651, 652, 652.1, 653, 654, 655, 655.3,
655.4, 655.9, 656, 657, 657.5, 663, 688,
690, 706, 710, 717, 718, 727, 731, 733,
736, 737, 739; 15/208, 209.1, 210.1; 128/849,
853, 854; D29/101.5

(56) **References Cited**

U.S. PATENT DOCUMENTS

D166,664 S * 5/1952 Godfrey D6/601
3,909,847 A * 10/1975 Holt et al. 2/466
4,014,044 A * 3/1977 Figueroa et al. 2/466
D277,316 S * 1/1985 Meares D24/190
D294,900 S * 3/1988 Willingham D6/601
4,807,301 A 2/1989 Ferber
4,811,427 A * 3/1989 Regan 2/466
4,914,762 A * 4/1990 Perali et al. 5/655.3
D348,544 S * 7/1994 Wharton D29/101.5
D356,705 S * 3/1995 Aston 5/653

D357,040 S 4/1995 Madrid
5,483,705 A * 1/1996 DiMatteo 2/466
5,551,082 A 9/1996 Stewart et al.
D377,575 S * 1/1997 Lowrey, Jr. et al. D6/596
5,625,895 A 5/1997 Sovereign
5,649,328 A 7/1997 Martin
D388,999 S * 1/1998 Murphy D6/613
D396,373 S * 7/1998 Reale D6/601
5,819,323 A * 10/1998 Edenfield 2/466
D413,476 S * 9/1999 Crawford D6/601
6,041,441 A 3/2000 Counts et al.

* cited by examiner

Primary Examiner—Doris V. Coles
Assistant Examiner—T. Chase Nelson


(57) **CLAIM**

The ornamental design for a tailbone cushion pad, as shown and described.

DESCRIPTION

FIG. 1 is a rear elevational view of the tailbone cushion pad of the present invention;
FIG. 2 is a front elevational view of the tailbone cushion pad of FIG. 1;
FIG. 3 is a right side elevational view of the tailbone cushion pad of FIG. 1, the left view being a mirror image thereof;
FIG. 4 is a top plan view of the tailbone cushion pad of FIG. 1;
FIG. 5 is a bottom plan view of the tailbone cushion pad of FIG. 1; and,
FIG. 6 is a front elevational view of the tailbone cushion pad of FIG. 1.
The broken line showing of a pair of shorts in FIG. 6 is for illustrative purposes only and forms no part of the claimed design.

1 Claim, 2 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4



FIG. 5




FIG. 6