



US00D464613S

(12) **United States Design Patent** (10) **Patent No.:** **US D464,613 S**
Weaver (45) **Date of Patent:** **** Oct. 22, 2002**

(54) **TIRE TREAD**

(75) Inventor: **Charles Bradford Weaver**, Greenville, SC (US)

(73) Assignee: **Michelin Recherche et Technique S.A.**, Granges-Paccot (CH)

(**) Term: **14 Years**

(21) Appl. No.: **29/150,697**

(22) Filed: **Nov. 27, 2001**

(51) **LOC (7) Cl.** **12-15**

(52) **U.S. Cl.** **D12/579**

(58) **Field of Search** D12/544, 546, D12/547, 549, 551, 553, 554, 555, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 579, 586, 588, 589, 590, 591, 595, 603; 152/209.1, 209.12, 209.13, 209.26, 209.27, 209.28

(56) **References Cited**

U.S. PATENT DOCUMENTS

D288,426 S * 2/1987 Konishi et al. D12/544
4,884,607 A * 12/1989 Mori 152/209.18
D307,120 S * 4/1990 Ingley et al. D12/561
5,105,864 A * 4/1992 Watanabe et al. 152/209.18
5,213,641 A * 5/1993 Tsuda et al. 152/209.9
D397,066 S 8/1998 Grosskopf et al. D12/151
D397,649 S 9/1998 Grosskopf et al. D12/147
D399,798 S 10/1998 Grosskopf et al. D12/147
D412,303 S 7/1999 Kemp, Jr. D12/147

FOREIGN PATENT DOCUMENTS

DE M 94 07 109 * 3/1995

OTHER PUBLICATIONS

Atlas Pacemark Radial GT Tire, 2000 Tread Design Guide, Jan. 2000, p. 13. 2/5.*
Cordovan Grand Spirit HR+4 Tire, 2000 Tread Design Guide, Jan. 2000, p. 22. 4/3.*

Jetzon Roadmark Premium Drive Tire, 2000 Tread Design Guide, Jan. 2000, p. 135. 4/4.*

Tread Design Guide, 1997, p. 214, Dunlop K525 Qualifier. Tread Design Guide, 2000, p. 33, Goodyear Eagle Aquasteel EMT.

Tread Design Guide, 2000. p. 40, Kelly-Springfield Charger HP Plus.

Tread Design Guide, 2000, p. 61, Sears Viper "Z".

Tread Design Guide, 2000, p. 69, Toyo Observe G03.

Tread Design Guide, 2000, p. 118, Yokohama Geolandar M/T.

* cited by examiner

Primary Examiner—Robert M. Spear

(74) *Attorney, Agent, or Firm*—Martin Farrell; Felipe Farley; Alan A. Csontos

(57) **CLAIM**

The ornamental design for a tire tread, as shown and described.


DESCRIPTION

FIG. 1 is a perspective view of a tire tread showing our new design, it being understood that the tread pattern repeats circumferentially throughout the circumference of the tire tread surface and shoulder of a tire, the opposite side perspective view being an inverted image thereto; and,

FIG. 2 is an enlarged fragmentary front elevation view of the tire tread thereof of FIG. 1.

In the drawings, the dark stippled surface shading represents the recessed portion of the tread grooves, having a depth as best shown along the right edge of FIG. 1. The broken line disclosure of the tire sidewall and inner bead is for illustrative purposes only and forms no part of the claimed design.

1 Claim, 2 Drawing Sheets






Fig. 1




Fig. 2