



US00D464865S

(12) **United States Design Patent**
Luu

(10) **Patent No.:** **US D464,865 S**

(45) **Date of Patent:** **** Oct. 29, 2002**

(54) **WALL PLATE HAVING AN ELECTROLUMINESCENT NIGHT LIGHT**

(75) Inventor: **Lionel V. Luu**, Anaheim, CA (US)

(73) Assignee: **Pacusma Company, Ltd.**, Kowloon (HK)

(**) Term: **14 Years**

(21) Appl. No.: **29/151,264**

(22) Filed: **Dec. 6, 2001**

Related U.S. Application Data

(62) Division of application No. 29/142,189, filed on May 22, 2001, which is a division of application No. 29/113,882, filed on Nov. 16, 1999, now Pat. No. Des. 443,500.

(51) **LOC (7) Cl.** **11-05**

(52) **U.S. Cl.** **D8/353; D26/26; D26/51**

(58) **Field of Search** **D8/350, 353; D13/177, D13/139.6, 137.3, 133, 146, 139.8, 139.5; D14/101, 107, 125, 242, 256; D26/51, 26; 174/66; 439/187, 536, 540, 490; 362/95, 226, 406; 220/241; 710/69; 361/118, 119, 117, 643**

(56) **References Cited**

U.S. PATENT DOCUMENTS

D212,760 S	11/1968	Bordner	D26/51
D230,274 S	2/1974	Pulos	D26/51
4,000,405 A	12/1976	Horwinski		
D281,417 S	11/1985	Guichard	D26/51
4,611,264 A	9/1986	Bradley	362/95
4,872,081 A	10/1989	Murphy et al.	361/118
D305,641 S	1/1990	DeLuca	D26/51
5,114,365 A	5/1992	Thompson et al.	174/66
5,414,587 A	5/1995	Kiser et al.	361/118
5,473,517 A	12/1995	Blackman	362/95
D366,339 S	1/1996	Waller	D26/51
5,484,309 A	1/1996	Howard et al.	439/107
D366,878 S	2/1996	Wakabayashi et al.	D14/242

5,622,424 A	4/1997	Brady	362/95
D395,314 S	6/1998	Oikawa	D14/242
D399,825 S	10/1998	Heung et al.	D13/139.9
D401,566 S	11/1998	Gesmondi et al.	D13/177
D407,072 S	3/1999	Gaule	D13/177
5,923,577 A	7/1999	Murphy	361/118
D421,741 S	3/2000	Lien	D13/139.8
D424,520 S	5/2000	Yu	D26/51

Primary Examiner—B. J. Bullock

(74) *Attorney, Agent, or Firm*—Dickstein Shapiro Morin & Oshinsky

(57) **CLAIM**

The ornamental design for a wall plate having an electroluminescent night light, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a preferred embodiment of the present invention, showing a wall plate having a built-in electroluminescent night light.

FIG. 2 is a front view of the wall plate shown in FIG. 1, showing the illumination area for the night light as the curved beveled surfaces at the top and bottom of the top portion of the wall plate and a housing for the switch for operating the night light provided on the top illumination surface.


FIG. 3 is a side view of the wall plate shown in FIG. 1, showing the beveled illumination surfaces of the night light in the top portion thereof, and the switch housing on the top illumination surface.

FIG. 4 is a bottom view of the wall plate shown in FIG. 1, whereby the bottom illumination surface of the night light can be seen; and,

FIG. 5 is a top view of the wall plate shown in FIG. 1, showing the top illumination surface of the night light, and also the on-off switch for the night light disposed in a respective housing therefor.

The outlet holes for receiving the prongs of Tan electric plug are shown in the figures as dashed lines and form no part of the inventive design.

1 Claim, 1 Drawing Sheet






FIG. 1




FIG. 2



FIG. 3




FIG. 4




FIG. 5