



US00D468654S

(12) **United States Design Patent**
Wünsch

(10) **Patent No.: US D468,654 S**
(45) **Date of Patent: ** Jan. 14, 2003**

(54) **SURFACE MOUNTED SENSOR**

(75) **Inventor: Wilfried Wünsch, Winnenden (DE)**

(73) **Assignee: Luxmate Controls GmbH, Dornbirn (AT)**

(**) **Term: 14 Years**

(21) **Appl. No.: 29/150,255**

(22) **Filed: Nov. 19, 2001**

(30) **Foreign Application Priority Data**

May 17, 2001 (DE) 401 04 636

(51) **LOC (7) Cl. 10-05**

(52) **U.S. Cl. D10/104**

(58) **Field of Search D10/104, 106;
250/340, 383, DIG. 1, 353, 342; 340/541-565**

(56) **References Cited**

U.S. PATENT DOCUMENTS

D358,109 S * 5/1995 Ozawa D10/104

D401,175 S * 11/1998 Bender et al. D10/104
D404,325 S * 1/1999 Bender et al. D10/104
6,051,836 A * 4/2000 Kirihata et al. 250/353
6,222,191 B1 * 4/2001 Myron et al. 250/353

* cited by examiner

Primary Examiner—Antoine Duval Davis

(74) *Attorney, Agent, or Firm*—Fitzpatrick, Cella, Harper & Scinto


(57) **CLAIM**

The ornamental design for a surface mounted sensor, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view showing the bottom (when mounted on a ceiling) and side of a design of a sensor forming a first embodiment of the invention; and, FIG. 2 is a perspective view showing the bottom (when mounted on a ceiling) and side of a design of a sensor forming a second embodiment of the invention.

1 Claim, 2 Drawing Sheets






FIG. 1




FIG. 2