



US00D468754S

(12) **United States Design Patent**  
**Dershem et al.**

(10) **Patent No.:** **US D468,754 S**

(45) **Date of Patent:** **\*\* Jan. 14, 2003**

(54) **SKID STEER LOADER EXTERIOR DESIGN**

(75) Inventors: **Brian R. Dershem**, Sanford, NC (US);  
**Reid W. Waitt**, Angier, NC (US); **Cary Safe**, Grand Rapids, MN (US); **Brad Lemke**, Grand Rapids, MN (US)

(73) Assignee: **Caterpillar S.A.R.L.**, Geneva

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/140,432**

(22) Filed: **Apr. 19, 2001**

(51) **LOC (7) Cl.** ..... **15-03**

(52) **U.S. Cl.** ..... **D15/28**

(58) **Field of Search** ..... D15/22-26, 28;  
414/697, 680, 685, 686, 700, 710; 209/38,  
235; 171/135, 74

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D230,300 S	*	2/1974	Gestman et al. ....	D15/28
D231,482 S		4/1974	Baner	
4,055,262 A		10/1977	Bauer et al.	
D272,825 S		2/1984	Cochran et al.	
D272,826 S		2/1984	Cochran et al.	
D314,389 S		2/1991	Lynnes et al.	
D317,926 S		7/1991	Lynnes et al.	
D322,792 S		12/1991	Park	
5,160,034 A	*	11/1992	Potter .....	209/28
5,240,366 A		8/1993	Bamford	
5,542,814 A		8/1996	Ashcroft et al.	

D376,372 S		12/1996	Little et al.	
5,807,061 A	*	9/1998	Donoghue .....	414/710
D407,418 S	*	3/1999	Miller et al. ....	D15/28
D419,568 S		1/2000	Baig et al.	
D423,521 S	*	4/2000	Walter et al. ....	D15/23

\* cited by examiner

*Primary Examiner*—Mitchell Siegel

(74) *Attorney, Agent, or Firm*—Sughrue; Diana L Charlton

(57) **CLAIM**


The ornamental design for a skid steer loader exterior design, as shown and described.

**DESCRIPTION**

FIG. 1 is a right side elevational view of a skid steer loader exterior design showing our new design; FIG. 2 is a left side elevational view thereof; FIG. 3 is a front elevational view thereof; FIG. 4 is a rear elevational view thereof; FIG. 5 is top plan elevational view thereof; and, FIG. 6 is a bottom plan view thereof.

Any broken line illustration of environmental structure in the drawings is not part of the design sought to be patented. A first characteristic feature of the design resides in the unique and corresponding alignment between the upper, rear curvature of the track and the lower, rear curvature of the frame. A second characteristic feature of the design resides in the unique rear to front inclination of the upper portion of the track and the boom arm that directs the line of sight toward the work implement.

**1 Claim, 6 Drawing Sheets**






FIG. 1




FIG. 2



FIG. 3.






FIG. 4.





5-5-03




FIG. 6