



US00D472795S

(12) **United States Design Patent**  
**Saxby**

(10) **Patent No.:** **US D472,795 S**

(45) **Date of Patent:** **\*\* Apr. 8, 2003**

(54) **POSITIONING DEVICE**

(76) **Inventor:** **George Saxby**, 61 Lorimer Crescent,  
Regina, SK (CA), S4R 3Y3

(\*\*) **Term:** **14 Years**

(21) **Appl. No.:** **29/163,181**

(22) **Filed:** **Jun. 28, 2002**

(51) **LOC (7) Cl.** ..... **08-05**

(52) **U.S. Cl.** ..... **D8/373; D8/367**

(58) **Field of Search** ..... D8/373, 367, 368;  
211/60.1, 106.01, 13.1, 65-66, 113, 123,  
118, 31-32, 85.3; 160/348, 349.2; 248/497,  
314, 489, 301-304, 216.1, 467, 339, 251,  
231.91, 205.3, 306, 317

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,232,094 A \* 2/1941 Canfield ..... 248/339  
2,693,864 A \* 11/1954 Ferro ..... 96/117.5  
2,788,438 A \* 4/1957 Lieuwen ..... 362/344

D328,562 S \* 8/1992 Lin ..... D8/373  
5,137,158 A \* 8/1992 Brockway ..... 211/106.01  
6,302,281 B1 \* 10/2001 Wang ..... 211/118

\* cited by examiner

*Primary Examiner*—Pamela Burgess

(57) **CLAIM**

The ornamental design for a positioning device, as shown and described.

**DESCRIPTION**

FIG. 1 is a front elevational view of a positioning device showing my new design;  
FIG. 2 is a rear elevational view thereof;  
FIG. 3 is a side view, taken from the left side of FIG. 1;  
FIG. 4 is a side view, taken from the right side of FIG.1;  
FIG. 5 is a top plan view thereof;  
FIG. 6 is a bottom plan view thereof; and,  
FIG. 7 is a front elevational view showing the parts of my design disassembled.

**1 Claim, 2 Drawing Sheets**




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7

