US00D473447S

(12) **United States Design Patent**
Luu

(10) **Patent No.: US D473,447 S**
(45) **Date of Patent: ** Apr. 22, 2003**

(54) **OVAL WALL PLATE**

(75) Inventor: **Daniel V. Luu**, Irving, TX (US)

(73) Assignee: **Pacusma Co., Ltd.**, Kowloon (HK)

(**) Term: **14 Years**

(21) Appl. No.: **29/150,039**

(22) Filed: **Nov. 1, 2001**

(51) **LOC (7) Cl.** **11-05**
(52) **U.S. Cl.** **D8/352**
(58) **Field of Search** D8/350, 352; D23/250–254; D13/177; 174/66; 220/241; 292/357; 439/536; 70/208; D6/524, 550

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,141,936	A *	12/1938	Schmitt	174/66
D153,803	S *	5/1949	Huppert	D8/352
D267,526	S *	1/1983	Figuered	D8/352
D317,691	S *	6/1991	Wang	D6/550
D355,021	S *	1/1995	Schott et al.	D23/254
D403,750	S *	1/1999	Fabian	D23/254
D405,995	S *	2/1999	Harris	D6/524
D423,911	S *	5/2000	Dagley	D8/352
D453,899	S *	2/2002	LaPlume et al.	D8/352

* cited by examiner

Primary Examiner—B. J. Bullock
(74) *Attorney, Agent, or Firm*—Dickstein Shapiro Morin & Oshinsky LLP

(57) **CLAIM**

The ornamental design for an oval wall plate, as shown and described.

DESCRIPTION

FIG. **1** is a right front perspective view of a first embodiment of the design, showing an oval wall plate having two concentric rings each having a tapered profile around its circumference, a central portion flush with the inner ring, and standard duplex receptacles for electrical plug sockets.

FIG. **2** is a front view of the wall plate shown in FIG. **1**.

FIG. **3** is a right side view of the wall plate shown in FIG. **1**.

FIG. **4** is an end view of the wall plate shown in FIG. **1**.

FIG. **5** is a cross-sectional view of the wall plate FIG. **1** as seen through the plane **5—5** in FIG. **2**.

FIG. **6** is a right front perspective view of a second embodiment of the design, showing an oval wall plate having two concentric rings each having a tapered profile around its circumference, a central portion recessed from the inner ring, and standard duplex receptacles for electrical plug sockets.

FIG. **7** is a front view of the wall plate shown in FIG. **6**.

FIG. **8** is a right side view of the wall plate shown in FIG. **6**.

FIG. **9** is an end view of the wall plate shown in FIG. **6**.

FIG. **10** is a cross-sectional view of the wall plate of FIG. **6** as seen through the plane **10—10** in FIG. **7**.

FIG. **11** is a right front perspective view of a third embodiment of the design, showing an oval wall plate having two concentric rings each having a tapered profile around its circumference, a central portion flush with the inner ring, and an opening sized and shaped to receive a set of decorative duplex electrical plug sockets.

FIG. **12** is a front view of the wall plate shown in FIG. **11**.

FIG. **13** is a right side view of the wall plate shown in FIG. **11**.

FIG. **14** is an end view of the wall plate shown in FIG. **11**.

FIG. **15** is a cross-sectional view of the wall plate of FIG. **11** as seen through the plane **15—15** in FIG. **12**.

FIG. **16** is a right front perspective view of a fourth embodiment of the design, showing an oval wall plate having two concentric rings each having a tapered profile around its circumference, a central portion recessed from the inner ring, and an opening sized and shaped to receive a set of decorative duplex electrical plug sockets.

FIG. **17** is a front view of the wall plate shown in FIG. **16**.

FIG. **18** is a right side view of the wall plate shown in FIG. **16**.

FIG. **19** is an end view of the wall plate shown in FIG. **16**.

FIG. **20** is a cross-sectional view of the wall plate of FIG. **16** as seen through the plane **20—20** in FIG. **17**.







FIG. **21** is a right front perspective view of a fifth embodiment of the design, showing an oval wall plate having a tapered outer ring and a flat inner ring, a central portion flush with the inner ring, and standard duplex receptacles for electrical plug sockets.

FIG. **22** is a front view of the wall plate shown in FIG. **21**.

FIG. **23** is a right side view of the wall plate shown in FIG. **21**.

FIG. **24** is an end view of the wall plate shown in FIG. **21**.

FIG. **25** is a cross-sectional view of the wall plate of FIG. **21** as seen through the plane **25—25** in FIG. **22**.

FIG. **26** is a right front perspective view of a sixth embodiment of the design, showing an oval wall plate having a tapered outer ring and a flat inner ring, a central portion recessed from the inner ring, and standard duplex receptacles for electrical plug sockets.

FIG. **27** is a front view of the wall plate shown in FIG. **26**.

FIG. **28** is a right side view of the wall plate shown in FIG. **26**.

FIG. **29** is an end view of the wall plate shown in FIG. **26**.

FIG. **30** is a cross-sectional view of the wall plate of FIG. **26** as seen through the plane **30—30** in FIG. **27**.

FIG. **31** is a right front perspective view of a seventh embodiment of the design, showing an oval wall plate having a tapered outer ring and a flat inner ring, a central portion flush with the inner ring, and an opening sized and shaped to receive a set of decorative duplex electrical plug sockets.

FIG. **32** is a front view of the wall plate shown in FIG. **31**.

FIG. **33** is a right side view of the wall plate shown in FIG. **31**.

FIG. **34** is an end view of the wall plate shown in FIG. **31**.

FIG. **35** is a cross-sectional view of the wall plate FIG. **31** as seen through the plane **35—35** in of FIG. **32**.

FIG. **36** is a right front perspective view of an eighth embodiment of the design, showing an oval wall plate having a tapered outer ring and a flat inner ring, a central portion recessed from the inner ring, and an opening sized and shaped to receive a set of decorative duplex electrical plug sockets.

FIG. **37** is a front view of the wall plate shown in FIG. **36**.

FIG. **38** is a right side view of the wall plate shown in FIG. **36**.

FIG. **39** is an end view of the wall plate shown in FIG. **36**.

FIG. **40** is a cross-sectional view of the wall plate of FIG. **36** as seen through the plane **40—40** in FIG. **37**.

FIG. **41** is a right front perspective view of a ninth embodiment of the design, showing an oval wall plate having an outer ring of varying width around it circumference, an inner ring of substantially constant width around it circumference, each ring having a tapered profile around its circumference, a central portion flush with the inner ring, and standard duplex receptacles for electrical plug sockets.

FIG. **42** is a front view of the wall plate shown in FIG. **41**.

FIG. **43** is a right side view of the wall plate shown in FIG. **41**.

FIG. **44** is an end view of the wall plate shown in FIG. **41**.

FIG. **45** is a cross-sectional view of the wall plate of FIG. **41** as seen through the plane **45—45** in FIG. **42**.

FIG. **46** is a right front perspective view of a tenth embodiment of the design, showing an oval wall plate having a tapered outer ring of varying width around it circumference, a tapered inner ring of substantially constant width around its circumference, a central portion recessed from the inner ring, and standard duplex receptacles for electrical plug sockets.

FIG. **47** is a front view of the wall plate shown in FIG. **46**.

FIG. **48** is a right side view of the wall plate shown in FIG. **46**.

FIG. **49** is an end view of the wall plate shown in FIG. **46**.

FIG. **50** is a cross-sectional view of the wall plate of FIG. **46** as seen through the plane **50—50** in FIG. **47**.

FIG. **51** is a right front perspective view of a, eleventh embodiment of the design, showing an oval wall plate having a tapered outer ring of varying width around its circumference, a tapered inner ring of constant width around its circumference, a central portion flush with the inner ring, and an opening sized and shaped to receive a set of decorative duplex electrical plug sockets.

FIG. **52** is a front view of the wall plate shown in FIG. **51**.

FIG. **53** is a front view of the wall plate shown in FIG. **51**.

FIG. **54** is an end view of the wall plate shown in FIG. **51**.

FIG. **55** is a cross-sectional view of the wall plate of FIG. **51** as seen through the plane **55—55** in FIG. **52**.

FIG. **56** is a right front perspective view of a twelfth embodiment of the design, showing an oval wall plate having a tapered outer ring of varying width around its circumference, a tapered inner ring of substantially constant width around its circumference, a central portion recessed from the inner ring, and an opening sized and shaped to receive a set of decorative duplex electrical plug sockets.

FIG. **57** is a front view of the wall plate shown in FIG. **56**.

FIG. **58** is a right side view of the wall plate shown in FIG. **56**.

FIG. **59** is an end view of the wall plate shown in FIG. **56**.

FIG. **60** is a cross-sectional view of the wall plate of FIG. **56** as seen through the plane **60—60** in FIG. **57**.

FIG. **61** is a right front perspective view of a thirteenth embodiment of the design, showing an oval wall plate having a flat outer ring of varying width around it circumference, a tapered inner ring of substantially constant width around its circumference, a central portion flush with the inner ring, and standard duplex receptacles for electrical plug sockets.

FIG. **62** is a front view of the wall plate shown in FIG. **61**.

FIG. **63** is a right side view of the wall plate shown in FIG. **61**.

FIG. **64** is an end view of the wall plate shown in FIG. **61**.

FIG. **65** is a cross-sectional view of the wall plate of FIG. **61** as seen through the plane **65—65** in FIG. **62**.

FIG. **66** is a right front perspective view of a fourteenth embodiment of the design, showing an oval wall plate having a tapered outer ring of varying width around it circumference, a flat inner ring of substantially constant width around its circumference, a central portion recessed from the inner ring, and standard duplex receptacles for electrical plug sockets.

FIG. **67** is a front view of the wall plate shown in FIG. **66**.

FIG. **68** is a front view of the wall plate shown in FIG. **66**.

FIG. **69** is an end view of the wall plate shown in FIG. **66**.

FIG. **70** is a cross-sectional view of the wall plate ofFIG. **66** as seen through the plane **70—70** in FIG. **67**.

FIG. **71** is a right front perspective view of a fifteenth embodiment of the design, showing an oval wall plate having a tapered outer ring of varying width around its circumference, a flat inner ring of substantially constant width around its circumference, a central portion flush with the inner ring, and an opening sized and shaped to receive a set of decorative duplex electrical plug sockets.

FIG. **72** is a front view of the wall plate shown in FIG. **71**.

FIG. **73** is a right side view of the wall plate shown in FIG. **71**.

FIG. **74** is an end view of the wall plate shown in FIG. **71**.

FIG. **75** is a cross-sectional view of the wall plate of FIG. **71** as seen through the plane **75—75** in FIG. **72**.

FIG. **76** is a right front perspective view of a sixteenth embodiment of the design, showing an oval wall plate having a tapered outer ring of varying width around its circumference, a flat inner ring of substantially constant width around its circumference, a central portion recessed from the inner ring, and an opening sided and shaped to recieve a set of decorative duplex electrical plug sockets.

FIG. **77** is a front view of the wall plate shown in FIG. **76**.

FIG. **78** is a right side view of the wall plate shown in FIG. **76**.

FIG. **79** is an end view of the wall plate shown in FIG. **77**.

FIG. **80** is a cross-sectional view of the wall plate of FIG. **16** as seen through the plane **80—80** in FIG. **77**.

FIG. **81**is a right front perspective view of a seventeenth embodiment of the design, showing an oval wall plate having a tapered outer ring of substantially constant width around its circumference, a tapered inner ring of varying width around its circumference, a central portion flush with the inner ring, and standard duplex receptacles for electrical plug sockets.

FIG. **82** is a front view of the wall plate shown in FIG. **81**.

FIG. **83** is a right side view of the wall plate shown in FIG. **81**.

FIG. **84** is an end view of the wall plate shown in FIG. **81**.

FIG. **85** is a cross-sectional view of the wall plate of FIG. **81** as seen through the plane **85—85** in FIG. **82**.

FIG. **86** is a right front perspective view of an eighteenth embodiment of the design, showing an oval wall plate having a tapered outer ring of substantially constant width around its circumference, a tapered inner ring of varying width around its circumference, a central portion recessed from the inner ring, and standard duplex receptacles for electrical plug sockets.

FIG. **87** is a front view of the wall plate shown in FIG. **86**.

FIG. **88** is a right side view of the wall plate shown in FIG. **86**.

FIG. **89** is an end view of the wall plate shown in FIG. **86**.

FIG. **90** is a cross-sectional view of the wall plate ofFIG. **86** as seen through the plane **90—90** in FIG. **87**.

FIG. **91** is a right front perspective view of a nineteenth embodiment of the design, showing an oval wall plate having a tapered outer ring of substantially constant width around its circumference, a tapered inner ring of varying width around its circumference, a central portion flush with the inner ring, and an opening sized and shaped to receive a set of decorative duplex electrical plug sockets.

FIG. **92** is a front view of the wall plate shown in FIG. **91**.

FIG. **93** is a right side view of the wall plate shown in FIG. **91**.

FIG. **94** is an end view of the wall plate shown in FIG. **91**.

FIG. **95** is a cross-sectional view of the wall plate of FIG. **91** as seen through the plane **95—95** in FIG. **92**.

FIG. **96** is a right front perspective view of a twentieth embodiment of the design, showing an oval wall plate having a tapered outer ring of substantially constant width around its circumference, a tapered inner ring of varying width around its circumference, a central portion recessed from the inner ring, and an opening sized and shaped to receive a set of decorative duplex electrical plug sockets.

FIG. **97** is a front view of the wall plate shown in FIG. **96**.

FIG. **98** is a right side view of the wall plate shown in FIG. **96**.

FIG. **99** is an end view of the wall plate shown in FIG. **96**; and

FIG. **100** is a cross-sectional view of the wall plate ofFIG. **96** as seen through the plane **100—100** in FIG. **97**.

1 Claim, 40 Drawing Sheets



FIG. 2



FIG. 1

FIG. 4

FIG. 5



FIG. 3



FIG. 7

FIG. 6

FIG. 9

FIG. 10



FIG. 8



FIG. 12



FIG. 11

FIG. 14

FIG. 15



FIG. 13



FIG. 17



FIG. 16



FIG. 19

FIG. 20



FIG. 18



FIG. 22



FIG. 21

FIG. 24

FIG. 25



FIG. 23



FIG. 27



FIG. 26

FIG. 29

FIG. 30



FIG. 28



FIG. 32



FIG. 31

FIG. 34



FIG. 35



FIG. 33



FIG. 37



FIG. 36

FIG. 39

FIG. 40



FIG. 38



FIG. 42



FIG. 41

FIG. 44

FIG. 45



FIG. 46



FIG. 47



FIG. 46

FIG. 49

FIG. 50



FIG. 48



FIG. 52



FIG. 51

FIG. 54

FIG. 55



FIG. 56



FIG. 57



FIG. 56

FIG. 59

FIG. 60



FIG. 58



FIG. 62



FIG. 61

FIG. 64

FIG. 65



FIG. 66



FIG. 67



FIG. 66

FIG. 69



FIG. 70



FIG. 68



FIG. 72



FIG. 71

FIG. 74

FIG. 75



FIG. 73



FIG. 77



FIG. 76

FIG. 79

FIG. 80



FIG. 78



FIG. 82



FIG. 81

FIG. 84

FIG. 85



FIG. 86



FIG. 87



FIG. 86

FIG. 89

FIG. 90



FIG. 88



FIG. 92



FIG. 91

FIG. 94

FIG. 95



FIG. 96



FIG. 97



FIG. 96



FIG. 99

FIG. 100



FIG. 9