



US00D473862S

(12) **United States Design Patent**
Tsukuda

(10) **Patent No.:** **US D473,862 S**

(45) **Date of Patent:** **** Apr. 29, 2003**

(54) **DATA INPUT AND OUTPUT DEVICE**

D443,613 S * 6/2001 Do et al. D14/345
D445,107 S * 7/2001 Kuwahara et al. D14/345

(75) Inventor: **Masabumi Tsukuda**, Chiba (JP)

* cited by examiner

(73) Assignee: **Seiko Instruments Inc.**, Chiba (JP)

Primary Examiner—Freda Nunn

(**) Term: **14 Years**

(74) *Attorney, Agent, or Firm*—Finnegan, Henderson, Farabow, Garrett, & Dunner LLP

(21) Appl. No.: **29/160,805**

(57) **CLAIM**

(22) Filed: **May 17, 2002**

The ornamental design for a data input and output device, as shown and described.

(30) **Foreign Application Priority Data**

Nov. 19, 2001 (JP) 2001-033830

DESCRIPTION

(51) **LOC (7) Cl.** **14-02**

FIG. 1 is a perspective view of the front, bottom and right side of a data input and output device showing my new design;

(52) **U.S. Cl.** **D14/345**

FIG. 2 is a front view thereof;

(58) **Field of Search** D14/341-346;

FIG. 3 is a rear view thereof;

D18/1, 2, 7; 178/18.01-18.03; 235/145 A, 145 R; 341/22, 23; 345/156, 168, 169, 172, 173, 87; 708/105

FIG. 4 is a left side view thereof;

FIG. 5 is a right side view thereof;

FIG. 6 is a top plan view thereof;

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,898,600 A * 4/1999 Isashi 708/105
D430,117 S * 8/2000 Sachs et al. D14/345
D442,953 S * 5/2001 Lassen D14/345

FIG. 7 is a bottom view thereof; and,

FIG. 8 is a perspective reference view with the lid in the close condition.

1 Claim, 6 Drawing Sheets





FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

