



US00D476437S

(12) **United States Design Patent** (10) **Patent No.:** **US D476,437 S**
Dalton et al. (45) **Date of Patent:** **** Jun. 24, 2003**

(54) **LIGHTING DEVICE**

(75) Inventors: **David R. Dalton**, Turramurra (AU);
Michael Squires, Ryde (AU); **Timothy J. Rugendyke**, Woy Woy (AU); **John R. Brown**, Mosman (AU)

(73) Assignee: **Eveready Battery Company, Inc.**, St. Louis, MO (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/164,021**

(22) Filed: **Jul. 17, 2002**

(30) **Foreign Application Priority Data**

Jan. 25, 2002 (AU) 0210/2002

(51) **LOC (7) Cl.** **26-02**

(52) **U.S. Cl.** **D26/37**

(58) **Field of Search** D26/37-50; 362/157,
362/158, 171, 172, 173, 183-208

(56) **References Cited**

U.S. PATENT DOCUMENTS

D423,129 S * 4/2000 Nakagawa D26/49

D449,395 S * 10/2001 Dalton et al. D26/49

* cited by examiner

Primary Examiner—Marcus A. Jackson

(74) *Attorney, Agent, or Firm*—Robert W. Welsh

(57) **CLAIM**

We claim the ornamental design for a lighting device, as shown.

DESCRIPTION

FIG. 1 is a view showing a front end, top, and a first side of the lighting device of the present invention;

FIG. 2 is a view showing the front end, bottom, and a second side of the lighting device of the present invention;

FIG. 3 is a view of the top of the lighting device of the present invention;

FIG. 4 is a view of the bottom of the lighting device of the present invention;


FIG. 5 is a view of the second side of the lighting device of the present invention;

FIG. 6 is a view of the first side of the lighting device of the present invention;

FIG. 7 is a view of the front end of the lighting device of the present invention; and,

FIG. 8 is a view of a back end of the lighting device of the present invention.

1 Claim, 4 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8