



US00D482038S

(12) **United States Design Patent** (10) **Patent No.:** **US D482,038 S**
Gustafsson (45) **Date of Patent:** **** Nov. 11, 2003**

(54) **STAND FOR PORTABLE EQUIPMENT**

(75) Inventor: **Anders Gustafsson**, Huddinge (SE)

(73) Assignee: **SeaCatch AB**, Huddinge (SE)

(**) Term: **14 Years**

(21) Appl. No.: **29/157,762**

(22) Filed: **Mar. 26, 2002**

(30) **Foreign Application Priority Data**

Oct. 22, 2001 (SE) 01-1691

(51) **LOC (7) Cl.** **14-02**

(52) **U.S. Cl.** **D14/447; D14/451**

(58) **Field of Search** D6/449, 450, 400,
D6/466-469, 475, 491, 492, 509; D14/434,
447, 451; 298/125.1, 127, 133, 177.1, 178.1,
179.1, 183.1, 346.01, 346.02, 188.2, 917-924

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,395,178	A	3/1995	Chvojcek	403/349
D395,640	S *	6/1998	Goodman et al.	D14/114
5,897,179	A	4/1999	Wade	312/223
D413,872	S *	9/1999	Jessen	D14/114
6,206,183	B1	3/2001	Helsel	206/1.7
D457,162	S *	5/2002	Hawkins et al.	D14/434
D471,558	S *	3/2003	Wada	D14/434

FOREIGN PATENT DOCUMENTS

DE	19942749	A1	3/2000
GB	2310595	A	9/1976
GB	2270253	A	3/1994

* cited by examiner

Primary Examiner—Cathron C. Brooks

(74) *Attorney, Agent, or Firm*—Jacobson Holman PLLC

(57) **CLAIM**

The ornamental design for a stand for portable equipment, as shown and described.

DESCRIPTION

The invention relates to a stand for portable equipment, e.g. a portable computer, said stand comprising a tray and a lid. Said tray comprises a set of first grooves for side support members and a set of second grooves for side support members, where said set of first grooves is arranged at an angle to said set of second grooves. The portable equipment is placed on said tray. At least one of said side support members is movable along said set of first grooves into contact with the portable equipment placed on said tray and at least another one of said side support members is movable along said set of second grooves into contact with the portable equipment placed on said tray. In this way the portable equipment will be securely fastened to the tray, even when the tray is moved. A lid is arranged on the tray to provide protection for the portable equipment during transport. A leg arrangement can be attached to the bottom of said tray.

FIG. 1 is a perspective view of a stand for portable equipment showing my new design;

FIG. 2 is a left side view thereof;

FIG. 3 is a right side view thereof;


FIG. 4 is a top plan view thereof;

FIG. 5 is a bottom plan view thereof;

FIG. 6 is a front view thereof; and,

FIG. 7 is a rear view thereof.

1 Claim, 7 Drawing Sheets






FIG.1




FIG. 2




FIG.3




FIG.4




FIG. 5




FIG.6




FIG. 7