

US00D482661S

(12) United States Design Patent (10) Patent No.:

Shotey et al.

US D482,661 S

** Nov. 25, 2003 (45) Date of Patent:

COVER FOR AN ELECTRICAL (54)RECEPTACLE

Inventors: Michael Shotey, Scottsdale, AZ (US); (75)Michael McConnaughy, Glendale, AZ

(US); Edgar W. Maltby, Mesa, AZ

(US)

Assignee: TayMac Corporation, Gilbert, AZ

(US)

This patent is subject to a terminal dis-Notice:

claimer.

14 Years Term:

Appl. No.: 29/092,022

Aug. 11, 1998 Filed:

(52)

(58)D13/177; D8/352, 353; 174/66, 67; 220/241, 3.8; 439/536

(56)**References Cited**

U.S. PATENT DOCUMENTS

1,713,101 A	* 5/1929	Starrett
3,437,738 A	* 4/1969	Wagner 174/66 X
3,828,113 A	* 8/1974	Bourne 174/66 X
3,840,692 A	* 10/1974	Wells
4,009,797 A	* 3/1977	Lee 220/241
4,355,198 A	* 10/1982	Gartland, Jr 174/66
4,631,354 A	* 12/1986	Boteler 174/66
4,717,358 A	* 1/1988	Chaundy 174/66 X
5,165,042 A		Klinger 174/67
D350,530 S	* 9/1994	Comerci et al D13/177
5,556,289 A	* 9/1996	Holbrook, Jr
D402,186 S	* 12/1998	Pearse

^{*} cited by examiner

Primary Examiner—Joel Sincavage

(74) Attorney, Agent, or Firm—Schmeiser, Olsen & Watts LLP

CLAIM (57)

The ornamental design for a cover for an electrical receptacle, as shown and described.

DESCRIPTION

The cover according to the inventive design is for use in partially covering the relatively flat or planar portion or portions of an electrical receptacle of the general types shown in the drawings. In the first six embodiments, the electrical receptable being covered by the covers according to the invention is a duplex receptacle. In the seventh preferred embodiments is illustrated for use with a decorator-type receptacle.

FIG. 1 is a front and upper right perspective view of a cover for an electrical outlet showing the first embodiment of our new design attached to an electrical receptacle;

FIG. 2 is a front and upper right exploded perspective view thereof;

FIG. 3 is a front elevational view thereof;

FIG. 4 is a right side elevational view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a front and upper right perspective view of the outlet cover portion of the first embodiment;

FIG. 7 is a front elevational view thereof;

FIG. 8 is a rear and upper left perspective view thereof;

FIG. 9 is a rear elevational view thereof;

FIG. 10 is a right side elevational view thereof;

FIG. 11 is a cross-sectional view thereof taken along line 11—11 of FIG. 7;

FIG. 12 is a top view thereof;

FIG. 13 is a cross sectional view thereof taken along line 13—13 of FIG. 9;

FIG. 14 is a front and upper right perspective view of a cover for an electrical outlet showing the second embodiment of our new design attached to an electrical receptacle;

FIG. 15 is a front and upper right exploded perspective view thereof;

FIG. 16 is a front elevational view thereof;

FIG. 17 is a right side elevational view thereof;

FIG. 18 is a top plan view thereof;

FIG. 19 is a front and upper right perspective view of the outlet cover portion of the second embodiment;

FIG. 20 is a front elevational view thereof;




FIG. 21 is a rear and upper left perspective view thereof;

FIG. 22 is a rear elevational view thereof;

FIG. 23 is a right side elevational view thereof;

FIG. 24 is a cross-sectional view thereof taken along line

24—24 of FIG. 20;

FIG. 25 is a top view thereof;

FIG. 26 is a cross sectional view thereof taken along line 26—26 of FIG. 22;

FIG. 27 is a front and upper right perspective view of a cover for an electrical outlet showing the third embodiment of our new design attached to an electrical receptacle;

FIG. 28 is a front and upper right exploded perspective view thereof;

FIG. 29 is a front elevational view thereof;

FIG. 30 is a right side elevational view thereof;

FIG. 31 is a top plan view thereof;

FIG. 32 is a front and upper right perspective view of the outlet cover portion of the third embodiment;

FIG. 33 is a front elevational view thereof;

FIG. 34 is a rear and upper left perspective view thereof;

FIG. 35 is a rear elevational view thereof;

FIG. 36 is a right side elevational view thereof;

FIG. 37 is a cross-sectional view thereof taken along line 37—37 of FIG. 33;

FIG. 38 is a top view thereof;

FIG. 39 is a cross sectional view thereof taken along line 39—39 of FIG. 35;

FIG. 40 is a front and upper right perspective view of a cover for an electrical outlet showing the fourth embodiment of our new design attached to an electrical receptacle;

FIG. 41 is a front and upper right exploded perspective view thereof;

FIG. 42 is a front elevational view thereof;

FIG. 43 is a right side elevational view thereof;

FIG. 44 is a top plan view thereof;

FIG. 45 is a front and upper right perspective view of the outlet cover portion of the fourth embodiment;

FIG. 46 is a front elevational view thereof;

FIG. 47 is a rear and upper left perspective view thereof;

FIG. 48 is a rear elevational view thereof;

FIG. 49 is a right side elevational view thereof;

FIG. 50 is a cross-sectional view thereof taken along line 50—50 of FIG. 46;

FIG. 51 is a top view thereof;

FIG. 52 is a cross sectional view thereof taken along line 52—52 of FIG. 48;

FIG. 53 is a front and upper right perspective view of a cover for an electrical outlet showing the fifth embodiment of our new design attached to an electrical receptacle;

FIG. 54 is a front and upper right exploded perspective view thereof;

FIG. 55 is a front elevational view thereof;

FIG. 56 is a right side elevational view thereof;

FIG. 57 is a top plan view thereof;

FIG. 58 is a front and upper right perspective view of the outlet cover portion of the fifth embodiment;

FIG. 59 is a front elevational view thereof;

FIG. 60 is a rear and upper left perspective view thereof;

FIG. 61 is a rear elevational view thereof;

FIG. 62 is a right side elevational view thereof;

FIG. 63 is a cross-sectional view thereof taken along line 63—63 of FIG. 59;

FIG. 64 is a top view thereof;

FIG. 65 is a cross sectional view thereof taken along line 65—65 of FIG. 61;

FIG. 66 is a front and upper right perspective view of a cover for an electrical outlet showing the sixth embodiment of our new design attached to an electrical receptacle;

FIG. 67 is a front and upper right exploded perspective view thereof;

FIG. 68 is a front elevational view thereof;

FIG. 69 is a right side elevational view thereof;

FIG. 70 is a top plan view thereof;

FIG. 71 is a front and upper right perspective view of the outlet cover portion of the sixth embodiment;

FIG. 72 is a front elevational view thereof;

FIG. 73 is a rear and upper left perspective view thereof;

FIG. 74 is a rear elevational view thereof;

FIG. 75 is a right side elevational view thereof;

FIG. 76 is a cross-sectional view thereof taken along line 76—76 of FIG. 72;

FIG. 77 is a top view thereof; and,

FIG. 78 is a cross sectional view thereof taken along line 78—78 of FIG. 74.


The claimed design is embodied in the assembled appearance of the outlet cover and the wall plate as shown in FIGS. 1, 14, 27, 40, 53 and 66. The outlet cover is shown separately in FIGS. 6–13, 19–26, 32–39, 45–52, 58–65 and 71–78 in order to disclose aspects of the design that are not apparent

For each of the various embodiments, the right and left views for that embodiment are the same, so only the right views are shown. Similarly, the top and bottom views for a given embodiment also the same, so only the top views are shown.

from the views showing the assembled members.

The broken lines showing the electrical receptacle throughout the drawings are included for the purpose of illustrating environmental structure only and form no part of the claimed design. The broken lines on the wall plate thoughout the drawings are included for the purpose of illustrating portions of the cover that form no part of the claimed design.

1 Claim, 12 Drawing Sheets






FIG. 3











FIG. 4


















FIG. 6








FIG. 8








FIG. 16




FIG. 15







FIG. 17










FIG. 23

FIG. 22







FIG. 25




FIG. 26













FIG. 29









FIG. 30










FIG. 42



FIG. 43







FIG. 41













FIG. 49

FIG. 48













FIG. 50







FIG. 55










FIG. 56





















FIG. 60











FIG. 68















FIG. 77






FIG. 71




FIG. 76




FIG. 73

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO. : Des. 482,661 S

Page 1 of 13

DATED : November 25, 2003

INVENTOR(S) : Shotey et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Drawings,

Please replace Drawings Figures 1-78 with the attached 12 sheets of drawings.

Signed and Sealed this

Fifth Day of October, 2004


JON W. DUDAS

Director of the United States Patent and Trademark Office

U.S. Patent

Nov. 25, 2003

Sheet 1 of 12






Fig. 3




Fig. 4







Fig. 2





U.S. Patent

Sheet 3 of 12






FIG. 16




FIG. 17




FIG. 15




Fig. 14

U.S. Patent D482,661 S Sheet 4 of 12 Nov. 25, 2003 24 ◀ 24 ◀ J FIG. 20 FIG. 23 FIG. 22 FIG. 25 FIG. 26

FIG. 24


FIG. 21

FIG. 19

U.S. Patent

Nov. 25, 2003

Sheet 5 of 12






Fig. 29




Fig. 30






Fig. 28





Sheet 6 of 12






FIG. 36




Fig. 35




Fig. 39




Fig. 32




Fig. 37





FIG. 34

U.S. Patent

Nov. 25, 2003

Sheet 7 of 12

D482,661 S



٠ ١٠١١٠ ١٠١١٠)




FIG. 42




FIG. 43





FIG. 41



U.S. Patent D482,661 S Nov. 25, 2003 Sheet 8 of 12 50 ← 50 → - J FIG. 46 FIG. 49 FIG. 48 FIG. 52 FIG. 51


FIG. 50

FIG. 47

FIG. 45

U.S. Patent

Sheet 9 of 12






FIG. 55







FIG. 56





U.S. Patent

Sheet 10 of 12






Fig. 62





Fig. 61








FIG. 58




FIG. 63







FIG. 60

U.S. Patent

Sheet 11 of 12











Fig. 69






FIG. 66

Fig. 73




FIG. 76

FIG. 71