



US00D482666S

(12) **United States Design Patent**  
**Kamada**

(10) **Patent No.:** **US D482,666 S**

(45) **Date of Patent:** **\*\* Nov. 25, 2003**

(54) **LIGHT EMITTING DIODE (LED)**

**DESCRIPTION**

(75) Inventor: **Kazuhiro Kamada**, Anan (JP)

(73) Assignee: **Nichia Corporation**, Anan (JP)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/161,376**

(22) Filed: **May 30, 2002**

(30) **Foreign Application Priority Data**

Nov. 30, 2001 (JP) ..... 2001-035248  
Nov. 30, 2001 (JP) ..... 2001-035249

(51) **LOC (7) Cl.** ..... **13-03**

(52) **U.S. Cl.** ..... **D13/182**

(58) **Field of Search** ..... D10/104, 114;  
D13/180, 182; D26/2; 257/98, 99; 362/241,  
249, 250, 806; 372/45

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,152,624 A \* 5/1979 Knaebel ..... 313/499  
D288,805 S \* 3/1987 Nishizawa ..... D13/180

(List continued on next page.)

**FOREIGN PATENT DOCUMENTS**

JP D798960 S 10/1990  
JP D799024 S 10/1990  
JP D799025 S 10/1990  
JP D799756 S 11/1990  
JP D924913 S 1/1996

**OTHER PUBLICATIONS**

LED/Photo IC L7140-10/S7141-10-50 Mbps, Product Guide, Jul. 2001, 2 pages, Cat. No. KPIC1039J04, Hamamatsu Hotonikusu Corporation, Japan.

*Primary Examiner*—Ted Shooman

*Assistant Examiner*—Selina Sikder

(74) *Attorney, Agent, or Firm*—Smith Patent Office

(57) **CLAIM**

I claim the ornamental design for the light emitting diode (LED), as shown and described.

FIG. 1 is a perspective view of a LED showing my new design;

FIG. 2 is a plan view of the LED according to the embodiment of FIG. 1;

FIG. 3 is a front elevational view of the LED according to the embodiment of FIG. 1;

FIG. 4 is a right view of the LED according to the embodiment of FIG. 1;

FIG. 5 is a bottom plan view of the LED according to the embodiment of FIG. 1;

FIG. 6 is a rear view of the LED according to the embodiment of FIG. 1;

FIG. 7 is a plan view of a LED according to another embodiment of my new design;

FIG. 8 is a front elevational view of the LED according to the embodiment of FIG. 7;

FIG. 9 is a right view of the LED according to the embodiment of FIG. 7;

FIG. 10 is a bottom plan view of the LED according to the embodiment of FIG. 7;

FIG. 11 is a rear view of the LED according to the embodiment of FIG. 7;

FIG. 12 is a plan view of the LED according to yet another embodiment of my new design;

FIG. 13 is a front elevational view of the LED according to the embodiment of FIG. 12;

FIG. 14 is a right view of the LED according to the embodiment of FIG. 12;

FIG. 15 is a bottom plan view of the LED according to the embodiment of FIG. 12;

FIG. 16 is a rear view of the LED according to the embodiment of FIG. 12;

FIG. 17 is a plan view of a LED according to yet another embodiment of my new design;


FIG. 18 is a front elevational view of the LED according to the embodiment of FIG. 17;

FIG. 19 is a right view of the LED according to the embodiment of FIG. 17;

FIG. 20 is a bottom plan view of the LED according to the embodiment of FIG. 17; and,

FIG. 21 is a rear view of the LED according to the embodiment of FIG. 17.

**1 Claim, 5 Drawing Sheets**



# US D482,666 S

Page 2

---

## U.S. PATENT DOCUMENTS

D289,037 S	*	3/1987	Nishizawa et al.	.....	D13/180	D432,095 S	*	10/2000	Seeger et al.	.....	D13/182
5,266,817 A	*	11/1993	Lin	.....	257/89	6,147,367 A	*	11/2000	Yang et al.	.....	257/88
5,564,819 A	*	10/1996	Yamaguchi	.....	362/241	6,386,733 B1	*	5/2002	Ohkohdo et al.	.....	362/249

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21