



US00D483319S

(12) **United States Design Patent** (10) **Patent No.:** **US D483,319 S**
Abe (45) **Date of Patent:** **** Dec. 9, 2003**

(54) **TIRE TREAD**

(75) Inventor: **Osamu Abe**, Akashi (JP)
(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/176,818**

(22) Filed: **Feb. 27, 2003**

(30) **Foreign Application Priority Data**

Oct. 24, 2002 (JP) 2002-029061
Oct. 24, 2002 (JP) 2002-029064

(51) **LOC (7) Cl.** **12-15**

(52) **U.S. Cl.** **D12/518**

(58) **Field of Search** D12/514, 515,
D12/517, 518, 519, 523, 527, 528, 531,
532; 152/209.1, 209.8, 209.9

(56) **References Cited**

U.S. PATENT DOCUMENTS

D376,779 S * 12/1996 Kuwajima et al. D12/518
D453,730 S * 2/2002 Weber D12/532

* cited by examiner

Primary Examiner—Robert M. Spear
(74) *Attorney, Agent, or Firm*—David L. King

(57) **CLAIM**

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire tread showing my new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof;

FIG. 4 the left side elevational view thereof;

FIG. 5 is an enlarged fragmentary front elevational view thereof;

FIG. 6 is a perspective view of a second embodiment of a tire tread showing my new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 7 is the front elevational view of the second embodiment;

FIG. 8 is a right side elevational view of the second embodiment;


FIG. 9 is a left side elevational view of the second embodiment; and,

FIG. 10 is an enlarged fragmentary front elevational view of the second embodiment.

In the drawings, the broken lines defining the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall are for illustrative purposes only and form no part of the claimed design.

The dark stippled surface shading represents the recessed portion of the tread grooves having a depth as best shown in FIG. 2.

1 Claim, 10 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6




FIG-7




FIG-8




FIG-9




FIG-10