



US00D488287S

(12) **United States Design Patent**
Berger

(10) **Patent No.:** **US D488,287 S**

(45) **Date of Patent:** **** Apr. 13, 2004**

(54) **SEAT BELT POSITIONER WITH IMPROVED FASTENER ARRAY**

DESCRIPTION

(75) Inventor: **Russell Berger**, Needham, MA (US)

(73) Assignee: **Constance F. Berger**, Naples, FL (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/181,843**

(22) Filed: **May 16, 2003**

(51) **LOC (7) Cl.** **02-07**

(52) **U.S. Cl.** **D2/624**

(58) **Field of Search** D2/624, 627, 628,
D2/629, 631, 632, 638; D11/200, 201, 212,
222, 226, 228, 231; 297/482; 2/300, 311,
312, 322, 268; 24/186, 198; 606/203

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,099,199	A	*	11/1937	Devendor et al.	24/198
3,086,529	A	*	4/1963	Munz et al.	606/203
D255,061	S	*	5/1980	Nichols	D2/638
D418,274	S	*	1/2000	Sartel	D2/627

* cited by examiner

Primary Examiner—Paula A. Mortimer

(74) *Attorney, Agent, or Firm*—Barlow, Josephs & Holmes, Ltd.

(57) **CLAIM**

The ornamental design for a seat belt positioner with improved fastener array, as shown and described.

FIG. 1 is a perspective view of a seat belt positioner with improved fastener array in an opened unfolded condition showing my new design;

FIG. 2 is a top plan view of thereof;

FIG. 3 is a bottom view thereof;

FIG. 4 is a left side elevational view thereof;

FIG. 5 is a right side elevational view thereof;

FIG. 6 is a front elevational view thereof;

FIG. 7 is a rear elevational view thereof;

FIG. 8 is an environmental view of the seat belt positioner with improved fastener array of FIG. 1 installed on a seat belt and folded over a shoulder belt for securing a passenger therein; the broken lines forming no part of the present invention;


FIG. 9 is a top view of a second alternative embodiment of a seat belt positioner with improved fastener array showing my new design, the bottom is disclosed in FIG. 3;

FIG. 10 is a top view of a third alternative embodiment of a seat belt positioner with improved fastener array showing my new design, the bottom is disclosed in FIG. 3;

FIG. 11 is a top view of the fourth alternative embodiment of a seat belt positioner with improved fastener array showing my new design, the bottom, top, side, and end views are the same as the embodiment of FIG. 1; and,

FIG. 12 is a top view of the fifth alternative embodiment of a seat belt positioner with improved fastener array showing my new design, the bottom is disclosed in FIG. 3.

1 Claim, 12 Drawing Sheets






FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4



FIGURE 5



FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11




FIGURE 12