



US00D488774S

(12) **United States Design Patent**
Zufall et al.

(10) **Patent No.:** **US D488,774 S**

(45) **Date of Patent:** **** Apr. 20, 2004**

(54) **RECHARGEABLE BATTERY**

6,184,655 B1 2/2001 Malackowski
6,331,761 B1 12/2001 Kumar et al.

(75) Inventors: **Scott W. Zufall**, Kalamazoo, MI (US);
David E. Hershberger, Kalamazoo, MI (US)

FOREIGN PATENT DOCUMENTS

DE 4406879 * 9/1995 H01M/2/30
WO WO 98/06144 2/1998

(73) Assignee: **Stryker Corporation**, Kalamazoo, MI (US)

OTHER PUBLICATIONS

(**) Term: **14 Years**

Color Copy of Brochure, "Cut the cord, Keep the power, Expanding your Cordless Capabilities, Stryker Instruments", Rev. Jul. 1995, (Front and Back Covers, p. 2 and p. 6).

(21) Appl. No.: **29/155,857**

(22) Filed: **Feb. 19, 2002**

* cited by examiner

(51) **LOC (7) Cl.** **13-02**

(52) **U.S. Cl.** **D13/103**

(58) **Field of Search** D13/103; 429/96-100,
429/159, 163, 176

Primary Examiner—Joel Sincavage

(74) *Attorney, Agent, or Firm*—Flynn, Thiel, Boutell & Tanis, P.C.

(56) **References Cited**

(57) **CLAIM**

U.S. PATENT DOCUMENTS


The ornamental design of a rechargeable battery, as shown and described.

| | | | |
|--------------|-----------|--------------------|---------|
| 4,641,076 A | 2/1987 | Linden | |
| 4,641,077 A | 2/1987 | Pascaloff | |
| D329,092 S | 9/1992 | Carusillo et al. | |
| 5,187,422 A | 2/1993 | Izenbaard et al. | |
| D335,277 S | * 5/1993 | Hattori | D13/103 |
| 5,207,697 A | 5/1993 | Carusillo et al. | |
| D379,795 S | 6/1997 | Pitzen et al. | |
| D383,435 S | * 9/1997 | Svetlik | D13/103 |
| 5,782,821 A | 7/1998 | Couch | |
| 5,792,573 A | 8/1998 | Pitzen et al. | |
| D403,298 S | 12/1998 | Hall et al. | |
| 5,900,719 A | * 5/1999 | Imura | 320/154 |
| D413,564 S | 9/1999 | Hershberger et al. | |
| D413,566 S | 9/1999 | McCombs | |
| 5,977,746 A | 11/1999 | Hershberger et al. | |
| D417,648 S | * 12/1999 | Clowers et al. | D13/103 |
| 6,018,227 A | 1/2000 | Kumar et al. | |
| D419,844 S | 2/2000 | McCombs | |
| D432,077 S | * 10/2000 | Zurwelle et al. | D13/103 |
| 6,160,376 A | 12/2000 | Kumar et al. | |
| 6,168,881 B1 | * 1/2001 | Fischer et al. | 429/97 |

DESCRIPTION

FIG. 1 is a pictorial view of the rechargeable battery of this invention;
FIG. 2 is a front view of the rechargeable battery of FIG. 1;
FIG. 3 is a rear view of the rechargeable battery of FIG. 1;
FIG. 4 is a left side view of the rechargeable battery of FIG. 1;
FIG. 5 is a right side view of the rechargeable battery of FIG. 1;
FIG. 6 is a top view of the rechargeable battery of FIG. 1;
FIG. 7 is a bottom view of the rechargeable battery of FIG. 1; and,
FIG. 8 is a fragment of FIG. 1.
The broken lines above the base in FIGS. 2, 3, 5 and 6 are included for the purpose of illustrating a portion of the battery that forms no part of the claimed design.

1 Claim, 8 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8