



US00D489521S

(12) **United States Design Patent**
Bacon

(10) **Patent No.:** **US D489,521 S**

(45) **Date of Patent:** **** May 11, 2004**

(54) **BALANCE STABILIZING FOOT ORTHOTIC**

(75) **Inventor:** **Perry Higginson Bacon**, Mission Hills, KS (US)

(73) **Assignee:** **Knit-Rite, Inc.**, Kansas City, KS (US)

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/179,234**

(22) **Filed:** **Apr. 7, 2003**

Related U.S. Application Data

(63) Continuation of application No. 29/168,988, filed on Oct. 10, 2002, now Pat. No. Des. 474,590, which is a continuation of application No. 09/682,028, filed on Jul. 11, 2001, now abandoned.

(51) **LOC (7) Cl.** **02-99**

(52) **U.S. Cl.** **D2/961**

(58) **Field of Search** D2/961; 36/43, 36/145-147, 154, 155, 166, 173, 174, 180

(56) **References Cited**

U.S. PATENT DOCUMENTS

357,942 A	*	2/1887	Russell	36/37
1,013,992 A	*	1/1912	Foster	36/173
D139,580 S	*	11/1944	Diamant	D2/961
3,169,326 A		2/1965	Butera		
3,825,017 A		7/1974	Scrima		
4,155,180 A		5/1979	Phillips		
4,232,457 A		11/1980	Mosher		
4,338,734 A		7/1982	Schwartz		
4,435,910 A		3/1984	Marc		
4,589,216 A		5/1986	Fuscone		
4,677,766 A		7/1987	Gudas		
4,681,114 A		7/1987	Lodispoto		
4,686,993 A		8/1987	Grumbine		
4,756,096 A		7/1988	Meyer		
4,791,736 A	*	12/1988	Phillips	36/117.5
D300,686 S	*	4/1989	Peterson	D2/961
4,934,073 A		6/1990	Robinson		
5,015,427 A		5/1991	Sosnow		
5,058,585 A		10/1991	Kendall et al.		
D329,129 S		9/1992	Brown		
D332,003 S		12/1992	Brown		

5,216,825 A		6/1993	Brum		
D341,021 S	*	11/1993	Brown	D2/961
5,359,791 A		11/1994	Prahl et al.		
D357,349 S	*	4/1995	Vasyli	D2/961
5,940,994 A		8/1999	Allen		
6,131,315 A		10/2000	Frye et al.		
6,170,176 B1		1/2001	Clough		
6,173,511 B1		1/2001	Perrault		
6,282,816 B1	*	9/2001	Rosendahl	36/44
D462,510 S	*	9/2002	Goodrich et al.	D2/961
6,484,419 B1	*	11/2002	Rohde et al.	36/10
D474,590 S	*	5/2003	Bacon	D2/961

* cited by examiner

Primary Examiner—Dominic Simone

(74) *Attorney, Agent, or Firm*—Hovey Williams LLP

(57) **CLAIM**

The ornamental design for a balance stabilizing foot orthotic, as shown and described.

DESCRIPTION

FIG. 1 is a side elevational view of a foot orthotic constructed in accordance with a preferred embodiment of the present invention and shown placed in a shoe and supporting a wearer's foot;

FIG. 2 is an isometric view of the foot orthotic, particularly showing the ridge around the arch and metatarsal areas in broken line for illustrative purposes only and the broken line showing thereof forms no part of the claimed design;

FIG. 3 is a top plan view of the foot orthotic;

FIG. 4 is a bottom view of the foot orthotic, particularly showing the raised heel area in broken line for illustrative purposes only and the broken line showing thereof forms no part of the claimed design;

FIG. 5 is a right side view of the foot orthotic;


FIG. 6 is a left side view of the foot orthotic;

FIG. 7 is a front view of the foot orthotic;

FIG. 8 is a rear view of the foot orthotic; and,

FIG. 9 is an exploded view of the foot orthotic, particularly showing the intermediate layer in broken line for illustrative purposes only and the broken line showing thereof forms no part of the claimed design.

1 Claim, 3 Drawing Sheets






Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.




Fig. 7.




Fig. 8.




Fig. 9.