



US00D491305S

(12) **United States Design Patent**
Copeland

(10) **Patent No.: US D491,305 S**

(45) **Date of Patent: ** Jun. 8, 2004**

(54) **FLASHLIGHT**

(76) Inventor: **Bruce William Copeland**, 5463
Pepperwood Ct., Stone Mountain, GA
(US) 30087

(**) Term: **14 Years**

(21) Appl. No.: **29/183,752**

(22) Filed: **Jun. 17, 2003**

(51) **LOC (7) Cl.** **26-02**

(52) **U.S. Cl.** **D26/49**

(58) **Field of Search** D26/37-50; 362/157,
362/158, 171-173, 183-208

(56) **References Cited**

U.S. PATENT DOCUMENTS

D455,513 S	*	4/2002	Galli	D26/49
D463,596 S	*	9/2002	McGaffigan	D26/49
D467,022 S	*	12/2002	Fritz	D26/49
D473,961 S	*	4/2003	Galli	D26/49

* cited by examiner

Primary Examiner—Marcus A. Jackson

(74) *Attorney, Agent, or Firm*—Barnes & Thornburg

(57) **CLAIM**

The ornamental design for a flashlight, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a flashlight in accordance with my design, with the button of the flashlight, which does not form part of my new design, illustrated in broken lines, note that the minor portion of the flashlight is shown in a 0° position relative to the major portion of the flashlight;

FIG. 2 is a side elevation view thereof, with the button of the flashlight, which does not form part of my new design, illustrated in broken lines;

FIG. 3 is a side elevation view of the side opposite to the side illustrated in FIG. 2;

FIG. 4 is a side elevation view of the side of the flashlight which is 90° from the side illustrated in FIG. 2, with the button of the flashlight, which does not form part of my new design, illustrated in broken lines;

FIG. 5 is a side elevation view of the side opposite to the side illustrated in FIG. 4, with the button of the flashlight, which does not form part of my new design, illustrated in broken lines;

FIG. 6 is a top plan view thereof, with the lights of the flashlight, which do not form part of my new design, illustrated in broken lines;


FIG. 7 is a bottom plan view thereof;

FIG. 8 is a perspective view thereof showing the minor portion of the flashlight having been rotated into a position that is approximately 45° relative to the major portion of the flashlight, with the lights and the button of the flashlight, which do not form part of my new design, illustrated in broken lines; and,

FIG. 9 is a perspective view thereof showing the minor portion of the flashlight having been rotated into a position that is approximately 90° relative to the major portion of the flashlight, with the lights and the button of the flashlight, which do not form part of my new design, illustrated in broken lines.

It should be appreciated that although the flashlight is herein shown with its minor portion positioned in three distinct rotated positions relative to the major portion of the flashlight (e.g., 0°, 45°, and 90°), the minor portion may be rotated to any position throughout 360° of rotation relative to the major portion.

1 Claim, 7 Drawing Sheets






Fig. 1




Fig. 2



Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9