

US00D491899S1

(12) **United States Design Patent** (10) **Patent No.:** **US D491,899 S**
Yagi (45) **Date of Patent:** **** Jun. 22, 2004**

(54) **LIGHT EMITTING DIODE**

(75) Inventor: **Tetsuya Yagi**, Anan (JP)

(73) Assignee: **Nichia Corporation**, Anan (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/191,319**

(22) Filed: **Oct. 7, 2003**

Related U.S. Application Data

(62) Division of application No. 29/161,015, filed on May 22, 2002.

(51) **LOC (7) Cl.** **13-03**

(52) **U.S. Cl.** **D13/180**

(58) **Field of Search** D13/104, 114,
D13/180, 182; D26/37; 174/52.2; 257/79,
88, 89, 93-96, 91, 98, 99, 100, 432, 433,
434, 678, 684, 698; 313/499, 500; 362/35,
226, 249, 287, 294, 800

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,152,624 A	5/1979	Knaebel	
4,959,761 A	9/1990	Critelli et al.	
D312,979 S	12/1990	Oesterheld et al.	
D314,919 S	2/1991	Villar	
5,045,895 A	9/1991	Yoshida et al.	
5,226,053 A	7/1993	Cho et al.	
RE36,614 E	3/2000	Lumbard et al.	
6,061,160 A *	5/2000	Maruyama	398/201
D432,095 S	10/2000	Seeger et al.	

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

JP	D1102760 S	3/2001
JP	D1128521 S	12/2001

OTHER PUBLICATIONS

High Power Full Color Chip Type LED, New Product Guide, Jan. 1998, 1 page, Cat. No. 980110, Nichia Chemical Industries, Ltd., Japan.

Surface Mount Type LED—Light Emitting Diode, Product Guide, May 2001, 6 pages, Cat. No. 01055K, Nichia Corporation, Japan.

Primary Examiner—Philip S. Hyder

Assistant Examiner—Selina Sikder

(74) *Attorney, Agent, or Firm*—Smith Patent Office

(57) **CLAIM**

I claim the ornamental design for a light emitting diode, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a light emitting diode showing my new design;

FIG. 2 is a top plan view of the light emitting diode according to the embodiment of FIG. 1;

FIG. 3 is a left side elevational view of the light emitting diode according to the embodiment of FIG. 1;

FIG. 4 is a front elevational view of the light emitting diode according to the embodiment of FIG. 1;

FIG. 5 is a right side elevational view of the light emitting diode according to the embodiment of FIG. 1;

FIG. 6 is a bottom plan view of the light emitting diode according to the embodiment of FIG. 1;

FIG. 7 is a rear elevational view of the light emitting diode according to the embodiment of FIG. 1;

FIG. 8 is a top plan view of the light emitting diode according to another embodiment of my new design;

FIG. 9 is a left side elevational view of the light emitting diode according to the embodiment of FIG. 8;


FIG. 10 is a front elevational view of the light emitting diode according to the embodiment of FIG. 8;

FIG. 11 is a right side elevational view of the light emitting diode according to the embodiment of FIG. 8;

FIG. 12 is a bottom plan view of the light emitting diode according to the embodiment of FIG. 8; and,

FIG. 13 is a rear elevational view of the light emitting diode according to the embodiment of FIG. 8.

1 Claim, 3 Drawing Sheets



U.S. PATENT DOCUMENTS			
6,180,962 B1 *	1/2001	Ishinaga	257/99
D437,798 S	2/2001	Kiba et al.	
D439,351 S	3/2001	Kiba et al.	
6,315,432 B1	11/2001	Kuo	
D453,745 S	2/2002	Suenaga	
6,345,903 B1 *	2/2002	Koike et al.	362/249
D477,580 S *	7/2003	Kamada	D13/182
6,611,049 B2 *	8/2003	Kobayakawa	257/676
6,624,491 B2 *	9/2003	Waitl et al.	257/434
* cited by examiner			




FIG. 1




FIG. 2




FIG. 3



FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13