

US00D492788S1

(12) **United States Design Patent**
Bird et al.

(10) **Patent No.:** **US D492,788 S**
(45) **Date of Patent:** **** Jul. 6, 2004**

(54) **PAIR OF OUTER SHELLS FOR AN ANKLE BRACE**

(75) Inventors: **John R. Bird**, St. Paul, MN (US);
Michael J. Frazer, Minneapolis, MN (US)

(73) Assignee: **Bird & Cronin, Inc.**, Eagan, MN (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/169,780**

(22) Filed: **Oct. 25, 2002**

(51) **LOC (7) Cl.** **24-04**

(52) **U.S. Cl.** **D24/192**

(58) **Field of Search** D24/190, 192;
602/27, 23, 1, 5, 6

(56) **References Cited**

U.S. PATENT DOCUMENTS

487,492 A	12/1892	Pugsley	
3,674,023 A	7/1972	Mann	
3,701,349 A	10/1972	Larson	
4,280,489 A	7/1981	Johnson, Jr.	
4,517,968 A	5/1985	Greene et al.	
4,572,169 A	2/1986	Mauldin et al.	
4,590,932 A	5/1986	Wilkerson	
4,628,945 A	12/1986	Johnson, Jr.	
4,630,600 A	12/1986	Spencer et al.	
4,693,239 A	9/1987	Clover, Jr.	
4,844,094 A	7/1989	Grim	
4,913,755 A	4/1990	Grim	
RE33,395 E	10/1990	Peters	
4,964,402 A	* 10/1990	Grim et al.	602/2
4,977,891 A	* 12/1990	Grim	602/27
5,007,416 A	4/1991	Burns et al.	
5,014,691 A	* 5/1991	Cueman et al.	602/27
5,027,801 A	7/1991	Grim	
5,031,607 A	7/1991	Peters	
5,038,762 A	8/1991	Hess et al.	
5,050,620 A	9/1991	Cooper	
5,069,202 A	12/1991	Prock	
5,078,128 A	1/1992	Grim et al.	

5,092,319 A	3/1992	Grim	
5,113,877 A	5/1992	Johnson, Jr. et al.	
5,125,400 A	* 6/1992	Johnson, Jr.	602/13
5,199,941 A	4/1993	Makinen	
5,209,722 A	5/1993	Miklaus et al.	
5,213,564 A	5/1993	Johnson, Jr. et al.	
RE34,661 E	7/1994	Grim	

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

CA	1320082	7/1993
EP	0 252 121 B1	1/1988
EP	0 770 369 A1	5/1997
WO	WO 88/09156	12/1988

Primary Examiner—Stella Reid

(74) *Attorney, Agent, or Firm*—Merchant & Gould P.C.

(57) **CLAIM**

The ornamental design for a pair of outer shells for an ankle brace, as shown and described.

DESCRIPTION

FIG. 1 is a bottom left perspective view of an outer shell of an ankle brace showing my new design, the outer shell shown being configured for placement against the outside of an ankle;

FIG. 2 is a front elevational view of FIG. 1;

FIG. 3 is a right side elevational view of FIG. 1;

FIG. 4 is a top plan view of FIG. 1;

FIG. 5 is a back elevational view of FIG. 1;

FIG. 6 is a bottom plan view of FIG. 1;

FIG. 7 is a bottom left perspective view of an outer shell of an ankle brace showing my new design, the outer shell shown being configured for placement against the inside of an ankle;

FIG. 8 is a front elevational view of FIG. 7;


FIG. 9 is a right side elevational view of FIG. 7;

FIG. 10 is a top plan view of FIG. 7;

FIG. 11 is a back elevational view of FIG. 7; and,

FIG. 12 is a bottom plan view of FIG. 7.

1 Claim, 6 Drawing Sheets



US D492,788 S

Page 2

U.S. PATENT DOCUMENTS

5,348,530 A	9/1994	Grim et al.		5,637,077 A	6/1997	Parker	
5,366,439 A	* 11/1994	Peters	602/27	5,656,226 A	8/1997	McVicker	
5,368,549 A	11/1994	McVicker		5,676,642 A	* 10/1997	Peters	602/27
5,389,065 A	2/1995	Johnson, Jr.		5,695,452 A	12/1997	Grim et al.	
5,445,602 A	* 8/1995	Grim et al.	602/27	5,713,837 A	2/1998	Grim et al.	
5,464,385 A	11/1995	Grim		5,716,335 A	2/1998	Iglesias et al.	
5,492,133 A	2/1996	McVicker		5,797,865 A	8/1998	McDavid, III	
5,501,659 A	3/1996	Morris et al.		5,951,504 A	9/1999	Iglesias et al.	
5,527,269 A	6/1996	Reithofer		5,971,946 A	10/1999	Quinn et al.	
5,577,998 A	11/1996	Johnson, Jr. et al.		6,007,506 A	12/1999	Heil	
5,620,413 A	4/1997	Olson		6,511,449 B2	* 1/2003	Burns et al.	602/13

* cited by examiner

FIG. 1




FIG. 4





FIG. 2




FIG. 3

FIG. 5





FIG. 6

FIG. 7




FIG. 10





FIG. 8




FIG. 9

FIG. 11





FIG. 12