



US00D494128S1

(12) **United States Design Patent**
Berger

(10) **Patent No.:** **US D494,128 S**

(45) **Date of Patent:** **** Aug. 10, 2004**

(54) **CUSHIONED STORAGE DEVICE FOR VEHICLE SEATS**

(75) **Inventor:** **Russell Berger**, Needham, MA (US)

(73) **Assignee:** **Constance F. Berger**, Naples, FL (US)

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/179,863**

(22) **Filed:** **Apr. 15, 2003**

(51) **LOC (7) Cl.** **12-16**

(52) **U.S. Cl.** **D12/416; D6/601**

(58) **Field of Search** 224/275, 584, 224/907, 153, 155; 297/129, 180.11, 188.2, 188.12, 195.1, 199, 219.1, 225, 228.1, 229, 452.41; D12/400, 415, 416, 423, 424; 296/37.15; D6/595-598, 601, 604, 611; D24/183; 5/630, 632-633, 636-638, 640, 644, 652, 652.1, 653, 654, 655, 655.3, 655.4, 655.9, 656, 657.5, 907, 945

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,765,480	A	*	10/1956	Mueller	5/655
2,952,856	A	*	9/1960	Ruff	5/640
D282,036	S	*	1/1986	Ritchie et al.	D6/595
D284,151	S	*	6/1986	Johnson	D6/596
D296,348	S	*	6/1988	Terrien	D21/809
5,182,828	A	*	2/1993	Alivizatos	D24/183
5,272,780	A	*	12/1993	Clute	5/632
5,310,245	A	*	5/1994	Lyszczasz	D6/596
5,359,739	A	*	11/1994	Rains et al.	5/632

D370,956	S	*	6/1996	Pery	D21/809
5,530,974	A	*	7/1996	Rains et al.	5/630
D389,359	S	*	1/1998	Nowak	D6/596
D408,676	S	*	4/1999	Straub et al.	D6/596
D446,675	S	*	8/2001	Straub	D6/596
D458,503	S	*	6/2002	Norman	D6/601
6,640,366	B1	*	11/2003	Draves	5/630
D485,724	S	*	1/2004	Morikawa	D6/601

* cited by examiner

Primary Examiner—James Gandy

Assistant Examiner—T. Chase Nelson

(74) *Attorney, Agent, or Firm*—Barlow, Josephs & Holmes, Ltd.


(57) **CLAIM**

The ornamental design for a cushioned storage device for vehicle seats, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a cushioned storage device for vehicle seats showing my new design; FIG. 2 is a top view of thereof; FIG. 3 is a bottom view thereof; FIG. 4 is a right side elevational view thereof; FIG. 5 is a left side elevational view thereof; FIG. 6 is a rear elevational view thereof; FIG. 7 is a front elevational view thereof; and, FIG. 8 is an environmental view of the cushioned storage device for vehicle seats of FIG. 1 positioned on a vehicle seat; the broken lines forming no part of the present invention.

1 Claim, 8 Drawing Sheets






FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7

FIGURE 8

