

US00D496483S1

(12) United States Design Patent (10) Patent No.:

Christianson

US D496,483 S

** Sep. 21, 2004 (45) Date of Patent:

CLIP-ON LAMP

Thomas R. Christianson, Napa, CA Inventor:

(US)

Assignee: ShowerTek, Inc., Napa, CA (US)

14 Years Term:

Appl. No.: 29/188,164

Aug. 13, 2003 Filed:

(52)

(58)

D26/39, 43, 44; 362/98, 99, 191, 281–287, 269, 396, 418, 419, 427, 428, 430, 197–199,

References Cited (56)

U.S. PATENT DOCUMENTS

D111,886	S	*	10/1938	Zagel
D293,029	S			Shwisha
D364,477	S	*	11/1995	Ryder D26/60
D391,381	S	*	2/1998	Yang D26/60
D452,026	S	*	12/2001	Naghi et al D26/60
D464,754	S	*	10/2002	Cavins
6,467,929	B 2	*	10/2002	Lee 362/191
2002/0131263	A 1	*	9/2002	Naghi et al 362/98

OTHER PUBLICATIONS

"Super-Bright LED Clip Light" #SE399CLR from Sharperimage.com, (c)2004 (1 page).*

Primary Examiner—Clare E Heflin (74) Attorney, Agent, or Firm—David Pressman

CLAIM (57)

The ornamental design for a clip-on lamp, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view taken from the front and above of a clip-on lamp including a ball-head and a holder-clamp according to my invention.

FIG. 2 is a front elevational view of the clip-on lamp.

FIG. 3 is a rear elevational view of the clip-on lamp.

FIG. 4 is a elevational view of the right side of the clip-on lamp showing its holding clamp in an open condition. The left side of the lamp is a mirror image of the right side.

FIG. 5 is a top view of the clip-on lamp.


FIG. 6 is a bottom view of the clip-on lamp.

FIG. 7 is a perspective view of the ball-head portion of the clip-on lamp, the holder-clamp being omitted for illustrative purposes only; and,

FIG. 8 is a perspective view of the holder-clamp portion of the clip-on lamp, the ball-head being omitted for illustrative purposes only.

A clip-on lamp comprises a spherical or ball-shaped hend with a transparent front window and two light-emitting diodes inside the window. The rear side of the head has a series of radial grooves to facilitate unscrewing the rear portion. The head is held at its side by two fork arms that flare up and out from a swivel ball. The swivel ball is in turn mounted in two short fork arms that extend up and are integral with a first leg of a two-legged clamp. The first leg has a projecting arm extending from the leg below its short fork arms. A second leg of the clamp is pivoted on the projecting arm and curves down to a padded foot which is matingly aligned with a padded foot on the first arm. An operating grip projects from the outside of the curved part of the second arm.

1 Claim, 7 Drawing Sheets



109

^{*} cited by examiner





Fig. 1






Fig. 3






Fig. 4



Sep. 21, 2004

Fig. 5






Fig. 7

