

US00D497547S1

(12) **United States Design Patent** (10) **Patent No.:** **US D497,547 S**  
**Kumakura et al.** (45) **Date of Patent:** **\*\* Oct. 26, 2004**

(54) **CONTAINER FOR DRY BATTERIES**

(75) Inventors: **Katsuhiko Kumakura**, Kyoto (JP);  
**Yoshikazu Yukami**, Yao (JP); **Masaru Kanda**, Nara (JP)

(73) Assignee: **Matsushita Electric Industrial Co., Ltd.**, Osaka (JP)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/185,116**

(22) Filed: **Jun. 23, 2003**

(30) **Foreign Application Priority Data**

Jan. 15, 2003 (JP) ..... 2003-000718

(51) **LOC (7) Cl.** ..... **09-03**

(52) **U.S. Cl.** ..... **D9/415**

(58) **Field of Search** ..... D9/415, 414, 418,  
D9/337, 341; 206/461-471, 806, 495, 778-783,  
703-705; 224/902

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D222,581 S	11/1971	Nakakuma	
D302,662 S	8/1989	Calcerano et al.	
4,958,731 A *	9/1990	Calcerano	206/705
5,143,215 A	9/1992	Hartley et al.	
5,735,404 A	4/1998	Kumakura et al.	
D394,207 S *	5/1998	Waterbury et al.	D9/415
D410,384 S *	6/1999	Gaffney et al.	D9/415
5,947,297 A *	9/1999	Aoki et al.	206/705
6,029,818 A *	2/2000	Kumakura et al.	206/469
D423,344 S	4/2000	Kumakura et al.	
6,050,415 A *	4/2000	Lind et al.	206/462
D423,928 S	5/2000	Kumakura et al.	
D427,523 S	7/2000	Calcerano	
D433,936 S *	11/2000	Pirro et al.	D9/415

6,244,444 B1	6/2001	Jacobus et al.	
D450,936 S *	11/2001	Bernes	D6/336
6,364,115 B1	4/2002	Casanova et al.	
D479,125 S	9/2003	Kumakura et al.	
D479,126 S	9/2003	Kumakura et al.	
D480,963 S *	10/2003	Lee	D9/415
D489,253 S *	5/2004	Kumakura et al.	D9/415

**FOREIGN PATENT DOCUMENTS**

JP	60-162365	10/1985
JP	D1070266	5/2000
WO	WO 02/38470	5/2002

\* cited by examiner

*Primary Examiner*—Prabhakar Deshmukh

(74) *Attorney, Agent, or Firm*—Brinks Hofer Gilson & Lione


(57) **CLAIM**

The ornamental design for a container for dry batteries, as shown and described.

**DESCRIPTION**

FIG. 1 is a top perspective view of a container for dry batteries of the present invention in a closed position;  
 FIG. 2 is a front view thereof;  
 FIG. 3 is a rear view thereof;  
 FIG. 4 is a first side view thereof;  
 FIG. 5 is a second side view thereof;  
 FIG. 6 is a top view thereof;  
 FIG. 7 is a bottom view thereof;  
 FIG. 8 is a top view of a first portion for the container for dry batteries of the present invention in an open position;  
 and,  
 FIG. 9 is a top view of a second portion for the container for dry batteries of the present invention in an open position.

**1 Claim, 8 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8




FIG. 9