

US00D497547S1

(12) **United States Design Patent** (10) **Patent No.:** **US D497,547 S**
Kumakura et al. (45) **Date of Patent:** **** Oct. 26, 2004**

(54) **CONTAINER FOR DRY BATTERIES**

(75) Inventors: **Katsuhiko Kumakura**, Kyoto (JP);
Yoshikazu Yukami, Yao (JP); **Masaru Kanda**, Nara (JP)

(73) Assignee: **Matsushita Electric Industrial Co., Ltd.**, Osaka (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/185,116**

(22) Filed: **Jun. 23, 2003**

(30) **Foreign Application Priority Data**

Jan. 15, 2003 (JP) 2003-000718

(51) **LOC (7) Cl.** **09-03**

(52) **U.S. Cl.** **D9/415**

(58) **Field of Search** D9/415, 414, 418,
D9/337, 341; 206/461-471, 806, 495, 778-783,
703-705; 224/902

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D222,581 S 11/1971 Nakakuma
- D302,662 S 8/1989 Calcerano et al.
- 4,958,731 A * 9/1990 Calcerano 206/705
- 5,143,215 A 9/1992 Hartley et al.
- 5,735,404 A 4/1998 Kumakura et al.
- D394,207 S * 5/1998 Waterbury et al. D9/415
- D410,384 S * 6/1999 Gaffney et al. D9/415
- 5,947,297 A * 9/1999 Aoki et al. 206/705
- 6,029,818 A * 2/2000 Kumakura et al. 206/469
- D423,344 S 4/2000 Kumakura et al.
- 6,050,415 A * 4/2000 Lind et al. 206/462
- D423,928 S 5/2000 Kumakura et al.
- D427,523 S 7/2000 Calcerano
- D433,936 S * 11/2000 Pirro et al. D9/415

- 6,244,444 B1 6/2001 Jacobus et al.
- D450,936 S * 11/2001 Bernes D6/336
- 6,364,115 B1 4/2002 Casanova et al.
- D479,125 S 9/2003 Kumakura et al.
- D479,126 S 9/2003 Kumakura et al.
- D480,963 S * 10/2003 Lee D9/415
- D489,253 S * 5/2004 Kumakura et al. D9/415

FOREIGN PATENT DOCUMENTS

- JP 60-162365 10/1985
- JP D1070266 5/2000
- WO WO 02/38470 5/2002

* cited by examiner

Primary Examiner—Prabhakar Deshmukh

(74) *Attorney, Agent, or Firm*—Brinks Hofer Gilson & Lione


(57) **CLAIM**

The ornamental design for a container for dry batteries, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of a container for dry batteries of the present invention in a closed position;
 FIG. 2 is a front view thereof;
 FIG. 3 is a rear view thereof;
 FIG. 4 is a first side view thereof;
 FIG. 5 is a second side view thereof;
 FIG. 6 is a top view thereof;
 FIG. 7 is a bottom view thereof;
 FIG. 8 is a top view of a first portion for the container for dry batteries of the present invention in an open position;
 and,
 FIG. 9 is a top view of a second portion for the container for dry batteries of the present invention in an open position.

1 Claim, 8 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9