

US00D501105S

(12) **United States Design Patent** (10) **Patent No.:** **US D501,105 S**
Post et al. (45) **Date of Patent:** **** Jan. 25, 2005**

(54) **PORTION OF MESH DRAWER AND FRAME**

(75) Inventors: **R. Neal Post**, Springfield, IL (US);
Christopher Hardy, Springfield, IL (US)

(73) Assignee: **Design Ideas, Ltd.**, Springfield, IL (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/190,480**

(22) Filed: **Sep. 22, 2003**

Related U.S. Application Data

(60) Division of application No. 29/176,610, filed on Feb. 27, 2003, now Pat. No. Des. 481,233, which is a continuation-in-part of application No. 29/148,906, filed on Sep. 28, 2001.

(51) **LOC (7) Cl.** **06-06**

(52) **U.S. Cl.** **D6/510; D6/465; D6/476**

(58) **Field of Search** D6/411, 415, 449, D6/455-469, 475, 476; 108/59, 91-94; 211/11, 13.1, 85.1, 85.2, 85.4, 70, 78, 107, 131, 133.2, 163-164, 181.1, 182

(56) **References Cited**

U.S. PATENT DOCUMENTS


297,382 A 4/1884 Golding
887,097 A 5/1908 Kimber
893,786 A 7/1908 Collins et al.
1,098,053 A 5/1914 Porter
RE16,431 E 9/1926 Kratzer
D152,141 S 12/1948 Crawford et al.
2,502,781 A 4/1950 Erickson
2,825,481 A 3/1958 Glenny
D182,349 S 4/1958 Alvord
2,905,519 A 9/1959 O'Neil
D189,544 S 1/1961 Harris
D189,550 S 1/1961 Alvord
D194,513 S 2/1963 Sparling
D204,314 S 4/1966 Bright
D207,308 S 4/1967 Bell

D227,964 S 7/1973 Propst
3,868,123 A 2/1975 Berg et al.
D267,395 S 12/1982 Groenewold et al.
4,509,805 A 4/1985 Welsch et al.
D300,488 S 4/1989 Yoshikawa
D303,444 S 9/1989 Yoshikawa
D328,993 S 9/1992 Rosenthal
D329,556 S 9/1992 Brüsing
D329,765 S 9/1992 Ackley et al.
D330,813 S 11/1992 Spitzer et al.
D340,369 S 10/1993 Dokoupil et al.
D341,459 S 11/1993 Yang
D360,531 S 7/1995 Griffith
D365,226 S 12/1995 Goebel
D370,144 S 5/1996 Insalaco et al.
D373,039 S 8/1996 Cohen et al.
5,605,344 A 2/1997 Insalaco et al.
5,673,984 A 10/1997 Insalaco et al.
5,685,442 A 11/1997 Yoshino et al.
5,810,179 A 9/1998 Kleiman
D408,175 S 4/1999 Daniels et al.
D409,866 S 5/1999 West
D411,045 S 6/1999 Morandi
D418,998 S 1/2000 Glassenberg
D419,302 S 1/2000 Hardy et al.
6,032,965 A 3/2000 Sabounjian
D430,375 S 8/2000 Tezak
D432,752 S 10/2000 Andujar et al.
D434,074 S 11/2000 Hardy
D436,239 S 1/2001 Walsh
D436,461 S 1/2001 Walker
D436,466 S 1/2001 Luong et al.
D438,402 S 3/2001 Walsh
D445,281 S 7/2001 Tsong-Yow
D450,481 S 11/2001 Post
D451,675 S 12/2001 Hardy et al.
D453,027 S 1/2002 Andujar
D455,029 S 4/2002 Gusdorf
D460,848 S 7/2002 Tzeng
D462,543 S 9/2002 Childers
D465,947 S 11/2002 Andersen et al.

OTHER PUBLICATIONS

The Container Store, The Ultimate Planning Guide, revised Nov. 2001.

The Container Store Catalog, Elfa Drawer Units, 1999, pp. 4, 5, 8, 10, 16, 17, 31.



1995 Design Ideas Catalogue, pp. cover page, 24, 26, 27 and 29.

1997 Design Ideas Holiday Catalogue, pp. cover page, 62 and 63.

HK Enterprise, Oct. 1999, p. 98, Item NH-11.

Primary Examiner—Cathron Brooks

(74) *Attorney, Agent, or Firm*—Saidman DesignLaw Group

(57) **CLAIM**

The ornamental design for a portion of mesh drawer and frame, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a first embodiment of a portion of mesh drawer and frame showing our new design, wherein 1- and 2-runner drawers are supported by a frame; FIG. 2 is a front view thereof, the rear view being identical thereto;

FIG. 3 is a side view thereof, the opposite side view being identical thereto;

FIG. 4 is a front view of a second embodiment thereof, wherein a 1-runner drawer is supported by a frame, the rear view being identical thereto;

FIG. 5 is a side view thereof, the opposite side view being identical thereto;

FIG. 6 is a top view of the embodiments of FIGS. 1-5, 16-23, 30, and 31;

FIG. 7 is a bottom view of the embodiments of FIGS. 4, 5, 16, 17, 20, and 21;

FIG. 8 is a front view of a third embodiment thereof wherein a 2-runner drawer is supported by a frame, the rear view being identical thereto;

FIG. 9 is a side view thereof, the opposite side view being identical thereto;

FIG. 10 is a top view of the embodiments of FIGS. 8, 9, and 24-27;

FIG. 11 is a bottom view of the embodiments of FIGS. 1-3, 8, 9, 24, 25, 30, and 31;

FIG. 12 is a front view of a fourth embodiment thereof, wherein a 3-runner drawer is supported by a frame, the rear view being identical thereto;

FIG. 13 is a side view thereof, the opposite side view being identical thereto;

FIG. 14 is a top view of the embodiments of FIGS. 12, 13, 28, and 29;

FIG. 15 is a bottom view of the embodiments of FIGS. 12, 13, 18, 19, 22, 23, and 26-29;

FIG. 16 is a front view of a fifth embodiment thereof, wherein two 1-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 17 is a side view thereof, the opposite side view being identical thereto;

FIG. 18 is a front view of a sixth embodiment thereof, wherein 1- and 3-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 19 is a side view thereof, the opposite side view being identical thereto;

FIG. 20 is a front view of a seventh embodiment thereof, wherein three 1-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 21 is a side view thereof, the opposite side view being identical thereto;

FIG. 22 is a front view of an eighth embodiment thereof wherein 1-, 2-, and 3-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 23 is a side view thereof, the opposite side view being identical thereto;

FIG. 24 is a front view of a ninth embodiment thereof, wherein two 2-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 25 is a side view thereof, the opposite side view being identical thereto;

FIG. 26 is a front view of a tenth embodiment thereof, wherein 2- and 3-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 27 is a side view thereof, the opposite side view being identical thereto;

FIG. 28 is a front view of an eleventh embodiment thereof, wherein two 3-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 29 is a side view thereof, the opposite side view being identical thereto;

FIG. 30 is a front view of a twelfth embodiment thereof, wherein a 1-runner drawer and two 2-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 31 is a side view thereof, the opposite side view being identical thereto;

FIG. 32 is a perspective view of a thirteenth embodiment of a portion of mesh drawer and frame showing our new design, wherein 1- and 2-runner drawers are supported by a frame;

FIG. 33 is a front view thereof, the rear view being identical thereto;

FIG. 34 is a side view thereof, the opposite side view being identical thereto;

FIG. 35 is a front view of a fourteenth embodiment thereof, the rear view being identical thereto;

FIG. 36 is a side view thereof, the opposite side view being identical thereto;

FIG. 37 is a top view of the embodiments of FIGS. 32-36, 47-54, and 61-62;

FIG. 38 is a bottom view of the embodiments of FIGS. 35, 36, and 47-48, and 51;

FIG. 39 is a front view of a fifteenth embodiment thereof, the rear view being identical thereto;

FIG. 40 is a side view thereof, the opposite side view being identical thereto;

FIG. 41 is a top view of the embodiments of FIGS. 39-40, and 55-58;

FIG. 42 is a bottom view of the embodiments of FIGS. 32-34, 39-40, 55-56, and 61-62;

FIG. 43 is a front view of a sixteenth embodiment thereof, the rear view being identical thereto;

FIG. 44 is a side view thereof, the opposite side view being identical thereto;

FIG. 45 is a top view of the embodiments of FIGS. 43-44 and 59-60;

FIG. 46 is a bottom view of the embodiments of FIGS. 43-44, 49-50, 53-54, and 57-60;

FIG. 47 is a front view of a seventeenth embodiment thereof, the rear view being identical thereto;

FIG. 48 is a side view thereof, the opposite side view being identical thereto;

FIG. 49 is a front view of an eighteenth embodiment thereof, the rear view being identical thereto;

FIG. 50 is a side view thereof, the opposite side view being identical thereto;

FIG. 51 is a front view of a nineteenth embodiment thereof, the rear view being identical thereto;

FIG. 52 is a side view thereof, the opposite side view being identical thereto;

FIG. 53 is a front view of a twentieth embodiment thereof, the rear view being identical thereto;

FIG. 54 is a side view thereof, the opposite side view being identical thereto;

FIG. 55 is a front view of a twenty-first embodiment thereof, the rear view being identical thereto;

FIG. 56 is a side view thereof, the opposite side view being identical thereto;

FIG. 57 is a front view of a twenty-second embodiment thereof, the rear view being identical thereto;

FIG. 58 is a side view thereof, the opposite side view being identical thereto;

FIG. 59 is a front view of a twenty-third embodiment thereof, the rear view being identical thereto;

FIG. 60 is a side view thereof, the opposite side view being identical thereto;

FIG. 61 is a front view of a twenty-fourth embodiment thereof, the rear view being identical thereto;

FIG. 62 is a side view thereof, the opposite side view being identical thereto; and,

FIG. 63 is an enlarged, fragmentary view of an exemplary wire mesh used in the foregoing embodiments of FIGS. 1-62.

The frames shown in broken lines are for environmental purposes only and form no part of the claimed design.

The jagged broken lines surrounding the somewhat U-shaped openings in the front and rear views of the drawers indicate that no particular handle shape is being claimed, represent boundaries of the claimed design and form no part of the claimed design.

The pairs of closely adjacent, spaced jagged broken lines in the drawings form no part of the claimed design and the portions between such pairs of jagged, broken lines are broken away to disclose indeterminate length. The mesh material that may be visible through each of the somewhat U-shaped openings, between the jagged lines, and through the holes in the mesh has been removed for clarity. The wavy end portions of the vertical frame members indicate fragmentary, indeterminate length and form no part of the claimed design.

1 Claim, 33 Drawing Sheets




FIG.1




FIG.3




FIG.2




FIG. 5




FIG. 4




FIG. 6




FIG. 7




FIG. 9




FIG. 8




FIG. 11




FIG. 10




FIG. 13




FIG. 12




FIG.15




FIG.14




FIG.17




FIG.16




FIG. 19




FIG. 18




FIG. 21




FIG. 20




FIG. 23




FIG. 22




FIG. 25




FIG. 24




FIG. 27




FIG. 26




FIG. 29




FIG. 28




FIG. 31




FIG. 30




FIG.32




FIG. 34




FIG. 33




FIG. 36




FIG. 35




FIG. 38




FIG. 37




FIG. 40




FIG. 39




FIG. 42




FIG. 41




FIG. 44




FIG. 43




FIG. 46




FIG. 45




FIG. 48




FIG. 47




FIG. 50




FIG. 49




FIG. 52




FIG. 51




FIG. 54




FIG. 53




FIG. 56




FIG. 55




FIG. 58




FIG. 57




FIG. 60




FIG. 59




FIG. 62




FIG. 61




FIG. 63