

US00D501105S

(12) **United States Design Patent** (10) **Patent No.:** **US D501,105 S**  
**Post et al.** (45) **Date of Patent:** **\*\* Jan. 25, 2005**

(54) **PORTION OF MESH DRAWER AND FRAME**

(75) Inventors: **R. Neal Post**, Springfield, IL (US);  
**Christopher Hardy**, Springfield, IL (US)

(73) Assignee: **Design Ideas, Ltd.**, Springfield, IL (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/190,480**

(22) Filed: **Sep. 22, 2003**

**Related U.S. Application Data**

(60) Division of application No. 29/176,610, filed on Feb. 27, 2003, now Pat. No. Des. 481,233, which is a continuation-in-part of application No. 29/148,906, filed on Sep. 28, 2001.

(51) **LOC (7) Cl.** ..... **06-06**

(52) **U.S. Cl.** ..... **D6/510; D6/465; D6/476**

(58) **Field of Search** ..... D6/411, 415, 449, D6/455-469, 475, 476; 108/59, 91-94; 211/11, 13.1, 85.1, 85.2, 85.4, 70, 78, 107, 131, 133.2, 163-164, 181.1, 182

(56) **References Cited**

**U.S. PATENT DOCUMENTS**


297,382 A 4/1884 Golding  
887,097 A 5/1908 Kimber  
893,786 A 7/1908 Collins et al.  
1,098,053 A 5/1914 Porter  
RE16,431 E 9/1926 Kratzer  
D152,141 S 12/1948 Crawford et al.  
2,502,781 A 4/1950 Erickson  
2,825,481 A 3/1958 Glenny  
D182,349 S 4/1958 Alvord  
2,905,519 A 9/1959 O'Neil  
D189,544 S 1/1961 Harris  
D189,550 S 1/1961 Alvord  
D194,513 S 2/1963 Sparling  
D204,314 S 4/1966 Bright  
D207,308 S 4/1967 Bell

D227,964 S 7/1973 Propst  
3,868,123 A 2/1975 Berg et al.  
D267,395 S 12/1982 Groenewold et al.  
4,509,805 A 4/1985 Welsch et al.  
D300,488 S 4/1989 Yoshikawa  
D303,444 S 9/1989 Yoshikawa  
D328,993 S 9/1992 Rosenthal  
D329,556 S 9/1992 Brüsing  
D329,765 S 9/1992 Ackley et al.  
D330,813 S 11/1992 Spitzer et al.  
D340,369 S 10/1993 Dokoupil et al.  
D341,459 S 11/1993 Yang  
D360,531 S 7/1995 Griffith  
D365,226 S 12/1995 Goebel  
D370,144 S 5/1996 Insalaco et al.  
D373,039 S 8/1996 Cohen et al.  
5,605,344 A 2/1997 Insalaco et al.  
5,673,984 A 10/1997 Insalaco et al.  
5,685,442 A 11/1997 Yoshino et al.  
5,810,179 A 9/1998 Kleiman  
D408,175 S 4/1999 Daniels et al.  
D409,866 S 5/1999 West  
D411,045 S 6/1999 Morandi  
D418,998 S 1/2000 Glassenberg  
D419,302 S 1/2000 Hardy et al.  
6,032,965 A 3/2000 Sabounjian  
D430,375 S 8/2000 Tezak  
D432,752 S 10/2000 Andujar et al.  
D434,074 S 11/2000 Hardy  
D436,239 S 1/2001 Walsh  
D436,461 S 1/2001 Walker  
D436,466 S 1/2001 Luong et al.  
D438,402 S 3/2001 Walsh  
D445,281 S 7/2001 Tsong-Yow  
D450,481 S 11/2001 Post  
D451,675 S 12/2001 Hardy et al.  
D453,027 S 1/2002 Andujar  
D455,029 S 4/2002 Gusdorf  
D460,848 S 7/2002 Tzeng  
D462,543 S 9/2002 Childers  
D465,947 S 11/2002 Andersen et al.

**OTHER PUBLICATIONS**

The Container Store, The Ultimate Planning Guide, revised Nov. 2001.

The Container Store Catalog, Elfa Drawer Units, 1999, pp. 4, 5, 8, 10, 16, 17, 31.



1995 Design Ideas Catalogue, pp. cover page, 24, 26, 27 and 29.

1997 Design Ideas Holiday Catalogue, pp. cover page, 62 and 63.

HK Enterprise, Oct. 1999, p. 98, Item NH-11.

*Primary Examiner*—Cathron Brooks

(74) *Attorney, Agent, or Firm*—Saidman DesignLaw Group

(57) **CLAIM**

The ornamental design for a portion of mesh drawer and frame, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of a first embodiment of a portion of mesh drawer and frame showing our new design, wherein 1- and 2-runner drawers are supported by a frame; FIG. 2 is a front view thereof, the rear view being identical thereto;

FIG. 3 is a side view thereof, the opposite side view being identical thereto;

FIG. 4 is a front view of a second embodiment thereof, wherein a 1-runner drawer is supported by a frame, the rear view being identical thereto;

FIG. 5 is a side view thereof, the opposite side view being identical thereto;

FIG. 6 is a top view of the embodiments of FIGS. 1-5, 16-23, 30, and 31;

FIG. 7 is a bottom view of the embodiments of FIGS. 4, 5, 16, 17, 20, and 21;

FIG. 8 is a front view of a third embodiment thereof wherein a 2-runner drawer is supported by a frame, the rear view being identical thereto;

FIG. 9 is a side view thereof, the opposite side view being identical thereto;

FIG. 10 is a top view of the embodiments of FIGS. 8, 9, and 24-27;

FIG. 11 is a bottom view of the embodiments of FIGS. 1-3, 8, 9, 24, 25, 30, and 31;

FIG. 12 is a front view of a fourth embodiment thereof, wherein a 3-runner drawer is supported by a frame, the rear view being identical thereto;

FIG. 13 is a side view thereof, the opposite side view being identical thereto;

FIG. 14 is a top view of the embodiments of FIGS. 12, 13, 28, and 29;

FIG. 15 is a bottom view of the embodiments of FIGS. 12, 13, 18, 19, 22, 23, and 26-29;

FIG. 16 is a front view of a fifth embodiment thereof, wherein two 1-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 17 is a side view thereof, the opposite side view being identical thereto;

FIG. 18 is a front view of a sixth embodiment thereof, wherein 1- and 3-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 19 is a side view thereof, the opposite side view being identical thereto;

FIG. 20 is a front view of a seventh embodiment thereof, wherein three 1-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 21 is a side view thereof, the opposite side view being identical thereto;

FIG. 22 is a front view of an eighth embodiment thereof wherein 1-, 2-, and 3-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 23 is a side view thereof, the opposite side view being identical thereto;

FIG. 24 is a front view of a ninth embodiment thereof, wherein two 2-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 25 is a side view thereof, the opposite side view being identical thereto;

FIG. 26 is a front view of a tenth embodiment thereof, wherein 2- and 3-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 27 is a side view thereof, the opposite side view being identical thereto;

FIG. 28 is a front view of an eleventh embodiment thereof, wherein two 3-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 29 is a side view thereof, the opposite side view being identical thereto;

FIG. 30 is a front view of a twelfth embodiment thereof, wherein a 1-runner drawer and two 2-runner drawers are supported by a frame, the rear view being identical thereto;

FIG. 31 is a side view thereof, the opposite side view being identical thereto;

FIG. 32 is a perspective view of a thirteenth embodiment of a portion of mesh drawer and frame showing our new design, wherein 1- and 2-runner drawers are supported by a frame;

FIG. 33 is a front view thereof, the rear view being identical thereto;

FIG. 34 is a side view thereof, the opposite side view being identical thereto;

FIG. 35 is a front view of a fourteenth embodiment thereof, the rear view being identical thereto;

FIG. 36 is a side view thereof, the opposite side view being identical thereto;

FIG. 37 is a top view of the embodiments of FIGS. 32-36, 47-54, and 61-62;

FIG. 38 is a bottom view of the embodiments of FIGS. 35, 36, and 47-48, and 51;

FIG. 39 is a front view of a fifteenth embodiment thereof, the rear view being identical thereto;

FIG. 40 is a side view thereof, the opposite side view being identical thereto;

FIG. 41 is a top view of the embodiments of FIGS. 39-40, and 55-58;

FIG. 42 is a bottom view of the embodiments of FIGS. 32-34, 39-40, 55-56, and 61-62;

FIG. 43 is a front view of a sixteenth embodiment thereof, the rear view being identical thereto;

FIG. 44 is a side view thereof, the opposite side view being identical thereto;

FIG. 45 is a top view of the embodiments of FIGS. 43-44 and 59-60;

FIG. 46 is a bottom view of the embodiments of FIGS. 43-44, 49-50, 53-54, and 57-60;

FIG. 47 is a front view of a seventeenth embodiment thereof, the rear view being identical thereto;

FIG. 48 is a side view thereof, the opposite side view being identical thereto;

FIG. 49 is a front view of an eighteenth embodiment thereof, the rear view being identical thereto;

FIG. 50 is a side view thereof, the opposite side view being identical thereto;

FIG. 51 is a front view of a nineteenth embodiment thereof, the rear view being identical thereto;

FIG. 52 is a side view thereof, the opposite side view being identical thereto;

FIG. 53 is a front view of a twentieth embodiment thereof, the rear view being identical thereto;

FIG. 54 is a side view thereof, the opposite side view being identical thereto;

FIG. 55 is a front view of a twenty-first embodiment thereof, the rear view being identical thereto;

FIG. 56 is a side view thereof, the opposite side view being identical thereto;

FIG. 57 is a front view of a twenty-second embodiment thereof, the rear view being identical thereto;

FIG. 58 is a side view thereof, the opposite side view being identical thereto;

FIG. 59 is a front view of a twenty-third embodiment thereof, the rear view being identical thereto;

FIG. 60 is a side view thereof, the opposite side view being identical thereto;

FIG. 61 is a front view of a twenty-fourth embodiment thereof, the rear view being identical thereto;

FIG. 62 is a side view thereof, the opposite side view being identical thereto; and,

FIG. 63 is an enlarged, fragmentary view of an exemplary wire mesh used in the foregoing embodiments of FIGS. 1-62.

The frames shown in broken lines are for environmental purposes only and form no part of the claimed design.

The jagged broken lines surrounding the somewhat U-shaped openings in the front and rear views of the drawers indicate that no particular handle shape is being claimed, represent boundaries of the claimed design and form no part of the claimed design.

The pairs of closely adjacent, spaced jagged broken lines in the drawings form no part of the claimed design and the portions between such pairs of jagged, broken lines are broken away to disclose indeterminate length. The mesh material that may be visible through each of the somewhat U-shaped openings, between the jagged lines, and through the holes in the mesh has been removed for clarity. The wavy end portions of the vertical frame members indicate fragmentary, indeterminate length and form no part of the claimed design.

**1 Claim, 33 Drawing Sheets**




FIG.1




FIG.3




FIG.2




FIG. 5




FIG. 4




FIG. 6




FIG. 7




FIG. 9




FIG. 8






FIG.10




FIG.11




FIG.13




FIG.12




FIG.15




FIG.14




FIG.17




FIG.16




FIG. 19




FIG. 18




FIG. 21




FIG. 20




FIG. 23




FIG. 22




FIG. 25




FIG. 24






FIG. 27




FIG. 26




FIG. 29




FIG. 28




FIG. 31




FIG. 30




FIG.32




FIG. 34




FIG. 33




FIG. 36




FIG. 35




FIG. 37




FIG. 38




FIG. 40




FIG. 39






FIG. 42




FIG. 41




FIG. 44




FIG. 43




FIG. 46




FIG. 45




FIG. 48




FIG. 47




FIG. 50




FIG. 49




FIG. 52




FIG. 51




FIG. 54




FIG. 53




FIG. 56




FIG. 55






FIG. 58




FIG. 57




FIG. 60




FIG. 59




FIG. 62





FIG. 61



**FIG. 63**