



US00D501473S

(12) **United States Design Patent**
Nakata

(10) **Patent No.:** **US D501,473 S**
(45) **Date of Patent:** **** Feb. 1, 2005**

(54) **COORDINATE INPUT DEVICE**

(75) Inventor: **Takaaki Nakata, Saitama (JP)**

(73) Assignee: **Wacom Co., Ltd., Saitama-ken (JP)**

(**) Term: **14 Years**

(21) Appl. No.: **29/197,469**

(22) Filed: **Jan. 16, 2004**

(30) **Foreign Application Priority Data**

Aug. 19, 2003 (JP) 2003-023850

(51) **LOC (7) Cl.** **14-02**

(52) **U.S. Cl.** **D14/341**

(58) **Field of Search** D14/341-346;
D18/1, 2, 7; 235/145 A, 145 R; 341/22,
23; 345/156, 168, 169, 172, 173; 349/12;
361/680-686

(56) **References Cited**

U.S. PATENT DOCUMENTS

D319,434 S * 8/1991 Lund D14/341
D346,366 S * 4/1994 Kim et al. D14/342

D346,591 S * 5/1994 Lee D14/342
D373,118 S * 8/1996 Naruki D14/342
D451,505 S * 12/2001 Iseki et al. D14/341

* cited by examiner

Primary Examiner—Freda S. Nunn

(74) *Attorney, Agent, or Firm*—Liniak, Berenato & White, LLC

(57) **CLAIM**

I claim, the ornamental design of a coordinate input device, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of a coordinate input device according to the invention, with the broken line showing indicating a removable component;
FIG. 2 is a bottom plan view thereof;
FIG. 3 is a right side elevational view;
FIG. 4 is a left side elevational view;
FIG. 5 is a rear elevational view;
FIG. 6 is a front elevational view; and,
FIG. 7 is a rear perspective view.

1 Claim, 5 Drawing Sheets




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7

