

US00D503139S

(12) **United States Design Patent**
Colak et al.

(10) **Patent No.:** **US D503,139 S**
(45) **Date of Patent:** **** Mar. 22, 2005**

(54) **WHEEL POSITIONAL RESTRAINT DEVICE**

(75) Inventors: **John I. Colak**, Edmonton (CA); **L. Reg Funk**, Edmonton (CA)

(73) Assignee: **Tri-Lynx Corporation**, Irving, TX (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/187,756**

(22) Filed: **Aug. 6, 2003**

Related U.S. Application Data

(63) Continuation-in-part of application No. 10/068,387, filed on Feb. 6, 2002, now Pat. No. 6,752,381.

(51) **LOC (7) Cl.** **12-16**

(52) **U.S. Cl.** **D12/217**

(58) **Field of Search** D12/217; 188/4 R;
280/293; 267/139, 140

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,162,973 A	12/1964	Christiansen	
3,487,579 A	1/1970	Brettingen	
3,752,441 A	8/1973	Rogers	
4,026,086 A	5/1977	Langley	
4,050,403 A	9/1977	Miller	
4,108,421 A	8/1978	Extine	
4,165,862 A	8/1979	Bennett	
4,427,179 A	1/1984	Price	
4,548,392 A	10/1985	Rickling	
4,606,732 A	8/1986	Lyman	
4,744,780 A	5/1988	Volpe	
D298,823 S	* 12/1988	Zutler	D12/217
4,819,910 A	4/1989	Johnston	
4,836,501 A	6/1989	Baer	
D307,575 S	* 5/1990	Gano	D12/217
D326,254 S	* 5/1992	Ziaylek et al.	D12/217

5,328,154 A	7/1994	Blatz et al.	
5,458,315 A	10/1995	Blatz et al.	
5,483,715 A	1/1996	Fogarty	
D409,554 S	* 5/1999	Henry	D12/217
D426,933 S	6/2000	Redfern	
6,439,543 B1	8/2002	Peckham	
D493,408 S	* 7/2004	Chrisco et al.	D12/217

FOREIGN PATENT DOCUMENTS

AU	242955	2/1960
CH	326589	7/1961
CZ	80935	9/1950
DE	1070420	12/1959
GB	1194445	6/1970
GB	2092792	* 6/2000
IT	374571	9/1939

* cited by examiner

Primary Examiner—Charles Rademaker

Assistant Examiner—Maurice Stevens

(74) *Attorney, Agent, or Firm*—Dykema Gossett PLLC

(57) **CLAIM**

The ornamental design for a wheel positional restraint device, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a wheel positional restraint device showing my new design.

FIG. 2 is a top plan view of the wheel positional restraint device shown in FIG. 1.


FIG. 3 is a front elevational view of the wheel positional restraint device shown in FIG. 1.

FIG. 4 is a side elevational view of the wheel positional restraint device shown in FIG. 1.

FIG. 5 is a rear elevational view of the wheel positional restraint device shown in FIG. 1; and,

FIG. 6 is a bottom plan view of the wheel positional restraint device shown in FIG. 1.

1 Claim, 2 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6