



US00D504583S

(12) **United States Design Patent** (10) **Patent No.:** **US D504,583 S**
Ritzel (45) **Date of Patent:** **** May 3, 2005**

(54) **RESTRAINT FOR A CHILD'S SEAT**

(75) Inventor: **Michael Ritzel**, Kirchheim unter Teck (DE)

(73) Assignee: **RECARO GmbH & Co. KG**, Kirchheim unter Teck (DE)

(**) Term: **14 Years**

(21) Appl. No.: **29/207,097**

(22) Filed: **Jun. 8, 2004**

(30) **Foreign Application Priority Data**

Dec. 9, 2003 (EP) 0000120514-0001

(51) **LOC (7) Cl.** **06-01**

(52) **U.S. Cl.** **D6/500**

(58) **Field of Search** D29/101.1, 101.4; D6/333, 356, 331, 339, 390, 391, 392, 500; 297/250.1, 484, 256.16; D12/129

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D315,453 S * 3/1991 Takada D6/333
- D325,132 S * 4/1992 Cone D6/333
- D338,343 S * 8/1993 Grange D6/333
- D353,057 S * 12/1994 Koyanagi et al. D6/333
- D353,947 S * 1/1995 Gain D6/333
- D355,986 S * 3/1995 Myers D6/356
- D361,743 S * 8/1995 Matsumoto et al. D12/129
- D369,911 S * 5/1996 Turner D6/333
- D376,872 S * 12/1996 Stroud D29/101.1
- D404,845 S * 1/1999 McIntyre et al. D29/101.1
- 5,964,502 A * 10/1999 Stephens 297/250.1
- 6,017,088 A * 1/2000 Stephens et al. 297/256.16
- D419,786 S * 2/2000 Kain D6/333
- D427,785 S * 7/2000 Kassai D6/333
- D433,540 S * 11/2000 Safaie-Brown D29/101.4
- D442,373 S * 5/2001 Ruehlmann et al. D6/333
- 6,543,847 B2 * 4/2003 Balensiefer 297/250.1
- 6,626,493 B2 * 9/2003 Kain 297/250.1
- 6,688,685 B2 * 2/2004 Kain 297/250.1
- 6,695,412 B2 * 2/2004 Barger et al. 297/484
- D487,640 S * 3/2004 Chen D6/333

6,779,843 B2 * 8/2004 Kain 297/250.1

* cited by examiner

Primary Examiner—Stacia Cadmus

Assistant Examiner—Terrence Huang

(74) *Attorney, Agent, or Firm*—Womble Carlyle Sandridge & Rice, PLLC

(57) **CLAIM**

The ornamental design for a restraint for a child's seat, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a restraint for a child's seat according to a first embodiment of the present invention; FIG. 2 is a front elevation view of the restraint for a child's seat shown in FIG. 1;

FIG. 3 is a left elevation view of the restraint for a child's seat shown in FIG. 1, with the right elevation view of the restraint for a child's seat shown in FIG. 1 being a mirror image of FIG. 3;

FIG. 4 is a top plan view of the restraint for a child's seat shown in FIG. 1;

FIG. 5 is a bottom plan view of the restraint for a child's seat shown in FIG. 1;

FIG. 6 is a rear elevation view of the restraint for a child's seat shown in FIG. 1;

FIG. 7 is a perspective view of a restraint for a child's seat according to a second embodiment of the present invention; FIG. 8 is a front elevation view of the restraint for a child's seat shown in FIG. 7;

FIG. 9 is a left elevation view of the restraint for a child's seat shown in FIG. 7, with the right elevation view of the restraint for a child's seat shown in FIG. 7 being a mirror image of FIG. 9;

FIG. 10 is top plan view of the restraint for a child's seat shown in FIG. 7;


FIG. 11 is a bottom plan view of the restraint for a child's seat shown in FIG. 7; and,

FIG. 12 is a rear elevation view of the restraint for a child's seat shown in FIG. 7.

The restraint for a child's seat is shown on a reduced scale in FIGS. 3 and 4.

The broken lines shown herein are for illustrative purposes only and form no part of the claimed design.

1 Claim, 12 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12