



US00D505159S

(12) **United States Design Patent**  
**Madigan et al.**

(10) **Patent No.:** **US D505,159 S**

(45) **Date of Patent:** **\*\* May 17, 2005**

(54) **EDUCATIONAL WALKING TRACK**

(76) Inventors: **Stephen Joseph Madigan**, 232 Zachary Walk, Murphy, TX (US) 75094;  
**Winifred Jean Madigan**, 232 Zachary Walk, Murphy, TX (US) 75094; **Larry Eugene Hess**, 307 E. 28th Division Hwy., Lititz, PA (US) 17543; **Cynthia Anne Hess**, 307 E. 28th Division Hwy., Lititz, PA (US) 17543

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/207,268**

(22) Filed: **Jun. 10, 2004**

(51) **LOC (7) Cl.** ..... **19-07**

(52) **U.S. Cl.** ..... **D19/60**

(58) **Field of Search** ..... D19/59, 60, 61, D19/62, 63, 64; D21/334, 338, 340, 800, 826; 182/181.1; 238/10 F; 273/236, 242, 254, 275, 287; 434/247, 255, 258; 482/34, 35, 36, 37, 38, 39, 41

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

- 1,916,809 A \* 7/1933 Patterson ..... 472/14
- 2,929,627 A \* 3/1960 Scanlon ..... 482/36
- 2,956,806 A \* 10/1960 Routson ..... 482/35
- 3,206,122 A \* 9/1965 Frisbie et al. .... 238/10 F

- 3,339,920 A \* 9/1967 Moritz ..... 482/34
- 3,545,747 A \* 12/1970 Thomas ..... 273/449
- D238,388 S \* 1/1976 Monroe ..... D21/338
- 3,944,654 A \* 3/1976 Moore ..... 482/34
- 5,211,366 A \* 5/1993 Cummings ..... 248/230.8
- 5,440,996 A \* 8/1995 Cottino ..... 104/47
- 5,554,074 A \* 9/1996 Von Parrish ..... 472/116
- 2003/0047420 A1 \* 3/2003 Snell et al. .... 198/495
- 2004/0009845 A1 \* 1/2004 Johnson ..... 482/41

\* cited by examiner

*Primary Examiner*—Nelson C. Holtje  
*Assistant Examiner*—Elizabeth Albert

(57) **CLAIM**

We claim the ornamental design for an educational walking track, as shown and described.

**DESCRIPTION**

The single FIGURE is a top plan view of the Educational Walking Track showing our new design. It is understood that the pair of shaded rails that make up the tracks are solid and that the unshaded narrow rungs connecting the tracks are also solid. Moreover the shaded platform in the middle where all the tracks intersect is also solid. All the areas between the platform, rails and rungs and all the areas between the tracks are understood to be open spaces. The tracks, made up of rails and rungs, and the platform are understood to have a minimal thickness.

**1 Claim, 1 Drawing Sheet**



