

US00D505424S

(12) **United States Design Patent** (10) **Patent No.:** **US D505,424 S**  
**Ashida et al.** (45) **Date of Patent:** **\*\* May 24, 2005**

(54) **CONTROLLER FOR ELECTRONIC GAME MACHINE**

5,797,569 A 8/1998 Simons  
 5,893,798 A \* 4/1999 Stambolic et al. .... 463/46  
 D413,360 S \* 8/1999 Smith ..... D14/400  
 D453,030 S \* 1/2002 Lutchen et al. .... D21/329

(75) Inventors: **Kenichiro Ashida**, Kyoto (JP); **Noboru Wakitani**, Kyoto (JP); **Junji Takamoto**, Kyoto (JP); **Kazuhiro Maruyama**, Kyoto (JP); **Nobutaka Nakajima**, Tokyo (JP); **Hiroshi Igarashi**, Tokyo (JP)

**OTHER PUBLICATIONS**

Musical Ctalog, Lark in the Morning, 1997 catalog, pp. 9 and 17.\*

\* cited by examiner

*Primary Examiner*—Prabhakar Deshmukh

(74) *Attorney, Agent, or Firm*—Nixon & Vanderhye P.C.

(73) Assignee: **Nintendo Co., Ltd.** (JP)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/200,678**

(22) Filed: **Mar. 4, 2004**

(57) **CLAIM**

The ornamental design for controller for electronic game machine, as shown and described.

(30) **Foreign Application Priority Data**

Sep. 9, 2003 (JP) ..... 2003-026282

(51) **LOC (7) Cl.** ..... **14-02**

(52) **U.S. Cl.** ..... **D14/401; D21/324; D21/333; D21/328**

(58) **Field of Search** ..... D14/400, 401, D14/412–416, 496, 432; D21/324, 328, 333; D17/22; 84/411 R, 415; D9/325; 273/148 B; 463/1, 29–35, 46, 47

**DESCRIPTION**

FIG. 1 is a front, right and top perspective view of a controller for electronic game machine showing our new design;

FIG. 2 is a rear, left and bottom perspective view thereof;

FIG. 3 is a front elevational view thereof;

FIG. 4 is a rear elevational view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom plan view thereof; and

FIG. 7 is a left side view thereof;

FIG. 8 is a right side view thereof;

FIG. 9 is a front, left and bottom perspective view thereof, showing in phantom a state that a cord is accommodated within grooves on a bottom surface; and,

FIG. 10 is the bottom plan view thereof, showing in phantom the state that the cord is accommodated within the grooves on the bottom surface.

The broken lines showing of cord in FIGS. 9 and 10 is for illustrative purpose only and form no part of the claimed design.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,420,233 A \* 6/1922 Baldwin et al. .... 84/411 R  
 D163,538 S \* 6/1951 Orta ..... D17/22  
 D265,877 S \* 8/1982 Hardy ..... D8/376  
 D325,662 S 4/1992 Meyers, Jr. et al.  
 5,168,969 A \* 12/1992 Mayhew ..... 191/12.2 R  
 5,329,837 A 7/1994 Appolonia, III  
 D357,271 S \* 4/1995 Hoshina ..... D17/22  
 5,645,277 A \* 7/1997 Cheng ..... 273/148 B  
 D384,110 S \* 9/1997 Stambolic et al. .... D21/324  
 5,667,220 A \* 9/1997 Cheng ..... 273/148 B

**1 Claim, 6 Drawing Sheets**




FIG. 1




FIG. 2



FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8






FIG. 9

FIG. 10

