

US00D506084S

(12) **United States Design Patent**
Beermann et al.

(10) **Patent No.: US D506,084 S**
(45) **Date of Patent: ** Jun. 14, 2005**

(54) **VEHICLE SEAT**

DESCRIPTION

- (75) Inventors: **Frank Beermann**, Kirchheim unter Teck (DE); **Dieter Armbrecht**, Kirchheim unter Teck (DE)
- (73) Assignee: **Recaro GmbH & Co. KG**, Kirchheim unter Teck (DE)
- (**) Term: **14 Years**
- (21) Appl. No.: **29/210,675**
- (22) Filed: **Aug. 4, 2004**
- (30) **Foreign Application Priority Data**
Feb. 11, 2004 (EM) 000138730
- (51) **LOC (8) Cl.** **06-01**
- (52) **U.S. Cl.** **D6/356**
- (58) **Field of Search** D6/334-336, 356, D6/367, 368, 374, 375, 500-502; 297/232, 391, 452.21, 452.24, 452.25, 452.26, 452.29, 452.34, 452.35, 354.1

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D356,694 S * 3/1995 Armbrecht D6/356
- D391,410 S * 3/1998 Tomforde et al. D6/356
- D396,152 S * 7/1998 Beermann et al. D6/356
- D440,062 S * 4/2001 Tsay D6/356
- D460,279 S * 7/2002 Moburg D6/356
- D465,344 S * 11/2002 Siegert D6/356
- D496,534 S * 9/2004 Pfeiffer D6/356

* cited by examiner

Primary Examiner—Mimosa De

(74) *Attorney, Agent, or Firm*—Womble Carlyle Sandridge & Rice, PLLC

(57) **CLAIM**

The ornamental design for a vehicle seat, as shown and described.

FIG. 1 is a perspective view of a vehicle seat according to a first embodiment of the present invention;
 FIG. 2 is a left elevation view of the vehicle seat shown in FIG. 1;
 FIG. 3 is a right elevation view of the vehicle seat shown in FIG. 1;
 FIG. 4 is a front elevation view of the vehicle seat shown in FIG. 1;
 FIG. 5 is a rear elevation view of the vehicle seat shown in FIG. 1;
 FIG. 6 is a top plan view of the vehicle seat shown in FIG. 1;
 FIG. 7 is a perspective view of a vehicle seat according to a second embodiment of the present invention;
 FIG. 8 is a left elevation view of the vehicle seat shown in FIG. 7;
 FIG. 9 is a right elevation view of the vehicle seat shown in FIG. 7;
 FIG. 10 is a front elevation view of the vehicle seat shown in FIG. 7;
 FIG. 11 is a rear elevation view of the vehicle seat shown in FIG. 7;
 FIG. 12 is a top plan view of the vehicle seat shown in FIG. 7;
 FIG. 13 is a perspective view of a vehicle seat according to a third embodiment of the present invention;
 FIG. 14 is a left elevation view of the vehicle seat shown in FIG. 13;
 FIG. 15 is a right elevation view of the vehicle seat shown in FIG. 13;
 FIG. 16 is a front elevation view of the vehicle seat shown in FIG. 13;
 FIG. 17 is a rear elevation view of the vehicle seat shown in FIG. 13; and,
 FIG. 18 is a top plan view of the vehicle seat shown in FIG. 13.

The broken lines shown herein are for illustrative purposes only and form no part of the claimed design.

1 Claim, 18 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6



FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12



FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18