

US00D506169S

(12) United States Design Patent (10) Patent No.:

Pfeiffer et al.

US D506,169 S

(45) Date of Patent: Jun. 14, 2005

SURFACE CONFIGURATION OF A SIDE (54)MIRROR FOR A VEHICLE

Inventors: Peter Pfeiffer, Boeblingen (DE);

Hans-Dieter Futschik, Gechingen (DE)

Assignee: DaimlerChrysler AG, Stuttgart (DE)

14 Years Term:

Appl. No.: 29/201,387

Mar. 16, 2004 (22)Filed:

Foreign Application Priority Data (30)

Oct.	15, 2003 (DE)		• • • • • • • • • • • • • • • • • • • •	4	103 06	633
(51)	LOC (8) C	1.		• • • • • • • • • • • • • • • • • • • •		12	-16
(52)	U.S. Cl			• • • • • • • • • • • • • • • • • • • •		D12 /	187
(58)	Field of Se	arch		• • • • • • • • • • • • • • • • • • • •	. D12/	187–1	89;
		359/830-	-856, 8	364–881;	248/4	75.1,	476

References Cited (56)

U.S. PATENT DOCUMENTS

D410,421	S *	6/1999	Pfeiffer D12/187
D428,840	S *	8/2000	Weidhase
D445,386	S *	7/2001	Sacco et al
D463,342	S *	9/2002	Sinkwitz
D464,922	S *	10/2002	Kuo D12/187
D484,837	S *	1/2004	Liu
D493,755	S *	8/2004	Kneefel et al D12/187
D496,616	S *	9/2004	Hoelzel et al D12/187

^{*} cited by examiner

Primary Examiner—Melody N. Brown

(74) Attorney, Agent, or Firm—Crowell & Moring LLP

(57)CLAIM

The ornamental design for a surface configuration of a side mirror for a vehicle, as shown and described.


DESCRIPTION


FIG. 1 is a rear perspective view of a first embodiment of a surface configuration of a side mirror for a vehicle according to our novel design;


- FIG. 2 is a front perspective view of the first embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 3 is a rear, elevated perspective view of the first embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 4 is a front view of the first embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 5 is a top view of the first embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 6 is a side view of the first embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 7 is a bottom view of the first embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 8 is a rear perspective view of a second embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 9 is a front perspective view of the second embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 10 is a rear, elevated perspective view of the second embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 11 is a front view of the second embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 12 is a top view of the second embodiment of the surface configuration of a side mirror for a vehicle according to our novel design;
- FIG. 13 is a side view of the second embodiment of the surface configuration of a side mirror for a vehicle according to our novel design; and,
- FIG. 14 is a bottom view of the second embodiment of the surface configuration of a side mirror for a vehicle according to our novel design.


The broken lines are for illustrative purposes only and form no part of the claimed design.


1 Claim, 8 Drawing Sheets














FIG. 6





FIG. 7








FIG. 9

Jun. 14, 2005








FIG. 13

