



US00D512690S

(12) **United States Design Patent**
Greene

(10) **Patent No.:** **US D512,690 S**
(45) **Date of Patent:** **** Dec. 13, 2005**

(54) **GUIDED INTRUSION DETECTION SWITCH HOUSING**

(75) Inventor: **Ted R. Greene**, San Diego, CA (US)

(73) Assignee: **United Security Products, Inc.**, San Diego, CA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/186,400**

(22) Filed: **Jul. 14, 2003**

(51) **LOC (6) Cl.** **13-03**

(52) **U.S. Cl.** **D13/158**

(58) **Field of Search** D13/158, 184;
200/61.7, 61.82, 61.93, 295; 335/205; 340/693.11

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,973,095	A	8/1976	Greene	
4,041,265	A *	8/1977	Brave et al.	200/534
4,057,773	A *	11/1977	Cohen	335/205
D253,106	S	10/1979	Holce	
D255,030	S	5/1980	Holce et al.	
4,213,110	A *	7/1980	Holce	335/207
D262,618	S	1/1982	Holce et al.	
4,384,181	A *	5/1983	Booden	200/61.76
4,553,134	A *	11/1985	Holt	340/546
4,700,163	A *	10/1987	Wolfe, Jr.	335/205
4,903,010	A	2/1990	Greene	
4,990,898	A *	2/1991	Greene	340/693.11
5,635,887	A *	6/1997	Fischette et al.	335/205
6,724,285	B1 *	4/2004	Zehrun	335/205

* cited by examiner

Primary Examiner—Prabhakar Deshmukh
Assistant Examiner—Selina Sikder
(74) *Attorney, Agent, or Firm*—Higgs Fletcher & Mack, LLP; Charles F. Reidelbach, Jr.

(57) **CLAIM**

The ornamental design for a guided intrusion detection switch housing, as shown.

DESCRIPTION

FIG. 1 is a front perspective view of the switch portion of the a guided intrusion detection switch housing of the present invention;

FIG. 2 is a top plan view of the switch portion of the a guided intrusion detection switch housing of FIG. 1;

FIG. 3 is a bottom plan view of the switch portion of the a guided intrusion detection switch housing of FIG. 1;

FIG. 4 is a front view in elevation of the switch portion of the a guided intrusion detection switch housing of FIG. 1;

FIG. 5 is a side view in elevation of the switch portion of a guided intrusion detection switch housing of FIG. 1 as seen from the right-hand side of FIG. 1;

FIG. 6 is a back view in elevation of the switch portion of the a guided intrusion detection switch housing of FIG. 1; FIG. 7 is a side view in elevation of the switch portion of the a guided intrusion detection switch housing of FIG. 1 as seen from the left-hand side of FIG. 1;

FIG. 8 is a front perspective view of the magnet portion of the a guided intrusion detection switch housing of the present invention;

FIG. 9 is a top plan view of the magnet portion of the a guided intrusion detection switch housing of FIG. 8;

FIG. 10 is a bottom plan view of the magnet portion of the a guided intrusion detection switch housing of FIG. 8;


FIG. 11 is a front view in elevation of the magnet portion of the a guided intrusion detection switch housing of FIG. 8;

FIG. 12 is a side view in elevation of the magnet portion of a guided intrusion detection switch housing of FIG. 8 as seen from the right-hand side of FIG. 8;

FIG. 13 is a back view in elevation of the magnet portion of the a guided intrusion detection switch housing of FIG. 8; and,

FIG. 14 is a side view in elevation of the magnet portion of the a guided intrusion detection switch housing of FIG. 8 as seen from the left-hand side of FIG. 8.

1 Claim, 2 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14