



US00D515245S

(12) **United States Design Patent**
Wartick

(10) **Patent No.: US D515,245 S**

(45) **Date of Patent: ** Feb. 14, 2006**

- (54) **MOTORCYCLE SAFETY BELT**
 - (76) Inventor: **Kent L. Wartick**, 5625 NE. Wygant,
Portland, OR (US) 97218
 - (**) Term: **14 Years**
 - (21) Appl. No.: **29/224,772**
 - (22) Filed: **Mar. 8, 2005**
 - (51) **LOC (8) Cl. 29-02**
 - (52) **U.S. Cl. D29/100; D29/101.5**
 - (58) **Field of Classification Search D29/100,**
D29/101.1, 101.2, 101.3, 101.4, 101.5; D2/627,
D2/629; D21/683; 2/16, 300, 311, 312, 321;
224/660
- See application file for complete search history.

- D356,659 S * 3/1995 Glass D29/101.5
- D366,555 S * 1/1996 Daniels D29/101.5
- D370,771 S * 6/1996 Randall D29/101.5
- D374,546 S * 10/1996 Luna D29/101.5
- 5,622,294 A * 4/1997 Evans 224/184
- 5,806,087 A 9/1998 Grotefend
- D410,958 S 6/1999 Curran
- 5,941,438 A * 8/1999 Price 224/660
- 6,345,745 B1 * 2/2002 Harriss 224/660
- D457,688 S * 5/2002 Cordero D29/100
- 6,567,992 B2 * 5/2003 Ross 2/311
- D480,535 S * 10/2003 Hammond D2/627
- D500,393 S * 12/2004 Beacham et al. D29/100

* cited by examiner

Primary Examiner—Gary D. Watson
Assistant Examiner—T. Chase Nelson

(56) **References Cited**
U.S. PATENT DOCUMENTS

- D32,350 S * 3/1900 Sanders D2/627
- 2,661,888 A * 12/1953 Sidlinger D2/627
- 2,709,257 A * 5/1955 McKinney 2/16
- 3,487,474 A 1/1970 DeMeo
- 3,562,812 A 2/1971 Greggains
- 3,840,902 A 10/1974 McNeill
- 3,896,499 A 7/1975 Kelly
- D238,315 S * 1/1976 Terwilleger D2/636
- 3,940,801 A * 3/1976 Riggs et al. 2/311
- 4,028,742 A 6/1977 Marquis
- D245,816 S * 9/1977 Conti et al. D29/101.5
- 4,411,222 A * 10/1983 Wolfson 2/300
- 4,413,358 A 11/1983 Jimenez
- 5,081,719 A 1/1992 Donnelly
- 5,152,013 A 10/1992 Johnson
- 5,201,448 A * 4/1993 Schue 2/300
- D336,566 S * 6/1993 Desjardins D29/101.1
- 5,388,274 A * 2/1995 Glover et al. 2/311

(57) **CLAIM**


The ornamental design for a motorcycle safety belt, as shown and described.

DESCRIPTION

A motorcycle driver safety belt with rear handles for a passenger to hold onto. The safety belt comprises of an adjustable leather belt, similar to that of a weight lifting belt, which goes around a driver's waist and has two rear safety handles. The safety handles are vertical to allow easy gripping by a passenger, enabling the passenger to ride safely and comfortably.

FIG. 1 is a front elevational view showing my design;
FIG. 2 is a rear view thereof;
FIG. 3 is a left side view thereof;
FIG. 4 is a right side view thereof; and,
FIG. 5 is a top plan view thereof.

1 Claim, 2 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5