



US00D516952S

(12) **United States Design Patent** (10) **Patent No.:** **US D516,952 S**
Kingsford et al. (45) **Date of Patent:** **** Mar. 14, 2006**

(54) **TOUCH FASTENER ELEMENT**

(75) Inventors: **Howard A. Kingsford**, Amherst, NH (US); **William L. Huber**, Pittsfield, NH (US); **Heidi S. Tremblay**, Windham, NH (US)

(73) Assignee: **Velcro Industries B.V.**, Curacao (AN)

(**) Term: **14 Years**

(21) Appl. No.: **29/186,169**

(22) Filed: **Jul. 10, 2003**

(51) **LOC (8) Cl.** **02-07**

(52) **U.S. Cl.** **D11/200; D8/383**

(58) **Field of Classification Search** D8/383,
D8/382; D11/200; 24/30.5 R, 445-446, 452;
428/100

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,339,499	A	8/1994	Kennedy et al.	
5,537,720	A *	7/1996	Takizawa et al.	24/452
5,702,797	A *	12/1997	Sakakibara et al.	428/100
5,900,350	A	5/1999	Provost et al.	
6,131,251	A *	10/2000	Provost	24/452
6,206,679	B1	3/2001	Provost et al.	
6,209,177	B1 *	4/2001	Murasaki	24/452

FOREIGN PATENT DOCUMENTS

EP EP 0 698 351 A2 2/1996

* cited by examiner

Primary Examiner—Holly H. Baynham
(74) *Attorney, Agent, or Firm*—Fish & Richardson P.C.

(57) **CLAIM**

The ornamental design for a touch fastener element, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a touch fastener element, with a bi-directional engaging portion and two relatively narrow side portions;

FIG. 2 is a top view of the touch fastener element of FIG. 1; FIG. 3 is a side view of the touch fastener element of FIG. 1;

FIG. 4 is an end view of the touch fastener element of FIG. 1;

FIG. 5 is a perspective view of a second embodiment of a touch fastener element, with a bi-directional engaging portion and one relatively narrow side portion;

FIG. 6 is a top view of the touch fastener element of FIG. 5; FIG. 7 is a side view of the touch fastener element of FIG. 5;

FIG. 8 is an end view of the touch fastener element of FIG. 5;

FIG. 9 is a perspective view of a third embodiment of a touch fastener element, with a bi-directional engaging portion and one relatively wide side portion;

FIG. 10 is a top view of the touch fastener element of FIG. 9;

FIG. 11 is a side view of the touch fastener element of FIG. 9;

FIG. 12 is an end view of the touch fastener element of FIG. 9;


FIG. 13 is a perspective view of a fourth embodiment of a touch fastener element, with a bi-directional engaging portion and two relatively wide side portions;

FIG. 14 is a top view of the touch fastener element of FIG. 13;

FIG. 15 is a side view of the touch fastener element of FIG. 13; and,

FIG. 16 is an end view of the touch fastener element of FIG. 13.

1 Claim, 4 Drawing Sheets






FIG. 1




FIG. 4




FIG. 2




FIG. 3




FIG. 5




FIG. 8




FIG. 6




FIG. 7




FIG. 9




FIG. 12




FIG. 10




FIG. 11




FIG. 13




FIG. 16




FIG. 14




FIG. 15