



US00D517710S

(12) **United States Design Patent**
Krieger et al.

(10) **Patent No.: US D517,710 S**
(45) **Date of Patent: ** Mar. 21, 2006**

(54) **FLASHLIGHT WITH BATTERY CHARGE LEVEL DISPLAY**

(75) Inventors: **Michael Krieger**, Miami Beach, FL (US); **Kevin Ellsworth**, Hollywood, FL (US)

(73) Assignee: **Vector Products, Inc.**, Ft. Lauderdale, FL (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/191,833**

(22) Filed: **Oct. 16, 2003**

(51) **LOC (8) Cl. 26-02**

(52) **U.S. Cl. D26/37**

(58) **Field of Classification Search** D26/37-50;
362/157, 158, 171-174, 183-208
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D466,242 S	11/2002	Chan	
D494,693 S	*	8/2004	Krieger et al. D26/37
D504,737 S	*	5/2005	Osiecki et al. D26/37
D507,064 S	*	7/2005	Osiecki et al. D26/37

* cited by examiner

Primary Examiner—Marcus A. Jackson
(74) *Attorney, Agent, or Firm*—Venable LLP; Robert Kinberg; Manni Li


(57) **CLAIM**

The ornamental design for a flashlight with battery charge level display, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view from the front-top-right side of the flashlight with battery charge level display showing a first embodiment of our new design; FIG. 2 is a front view of the design shown in FIG. 1; FIG. 3 is a rear view of the design shown in FIG. 1; FIG. 4 is a left side view of the design shown in FIG. 1; FIG. 5 is a right side view of the design shown in FIG. 1; FIG. 6 is a top view of the design shown in FIG. 1; FIG. 7 is a bottom view of the design shown in FIG. 1; FIG. 8 is a perspective view from the front-top-right side of the flashlight with battery charge level display showing a second embodiment of our new design; FIG. 9 is a front view of the design shown in FIG. 8; FIG. 10 is a rear view of the design shown in FIG. 8; FIG. 11 is a left side view of the design shown in FIG. 8; FIG. 12 is a right side view of the design shown in FIG. 8; FIG. 13 is a top view of the design shown in FIG. 8; FIG. 14 is a bottom view of the design shown in FIG. 8; FIG. 15 is a perspective view from the front-top-right side of the flashlight with battery charge level display showing a third embodiment of our new design; FIG. 16 is a front view of the design shown in FIG. 15; FIG. 17 is a rear view of the design shown in FIG. 15; FIG. 18 is a left side view of the design shown in FIG. 15; FIG. 19 is a right side view of the design shown in FIG. 15; FIG. 20 is a top view of the design shown in FIG. 15; and, FIG. 21 is a bottom view of the design shown in FIG. 15. The broken lines immediately adjacent the shaded areas represent the bounds of the claimed design while all other broken lines are for illustrative purposes only; the broken lines form no part of the claimed design.

1 Claim, 18 Drawing Sheets






FIG. 1




FIG. 3




FIG. 2




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 10




FIG. 9




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 17




FIG. 16




FIG. 18




FIG. 19




FIG. 20




FIG. 21