



US00D517770S

(12) **United States Design Patent** (10) **Patent No.:** **US D517,770 S**
Walker (45) **Date of Patent:** **** *Mar. 21, 2006**

(54) **SAFE**
(76) Inventor: **James Walker**, 2224 Wellesley Ave.,
Los Angeles, CA (US) 90064
(*) Notice: This patent is subject to a terminal dis-
claimer.
(**) Term: **14 Years**
(21) Appl. No.: **29/215,268**
(22) Filed: **Oct. 16, 2004**
(51) **LOC (8) Cl.** **99-00**
(52) **U.S. Cl.** **D99/28; D99/35**
(58) **Field of Classification Search** **D99/28,**
D99/34, 35; D6/432, 444, 448, 509, 510,
D6/559; 232/43.2, 43.3; 109/35, 45, 51, 64,
109/73, 39; 220/3.3; 70/158, 159, 416, 160-164;
190/19
See application file for complete search history.

5,405,196 A 4/1995 Shoup
5,608,609 A 3/1997 Morrell
5,667,288 A 9/1997 Kang
5,769,006 A * 6/1998 Allaer 109/73
5,890,439 A 4/1999 McGunn
D409,352 S * 5/1999 Nolte et al. D99/28
D412,797 S * 8/1999 Sadler D6/448
6,042,207 A 3/2000 Crosby
6,089,685 A 7/2000 Ryan
6,158,833 A 12/2000 Engler
6,164,219 A 12/2000 Green
D471,377 S * 3/2003 Gledhill et al. D6/432
6,621,707 B1 9/2003 Ishimine
D485,041 S * 1/2004 Paris et al. D99/28
2002/0062767 A1 5/2002 Walker

FOREIGN PATENT DOCUMENTS

GB 2066869 A 9/1979

* cited by examiner

Primary Examiner—Paula A. Greene
(74) *Attorney, Agent, or Firm*—Michael Zarrabian

(56) **References Cited**

U.S. PATENT DOCUMENTS

342,003 A 5/1886 Gross
928,483 A 7/1909 Wakeman
1,054,325 A 2/1913 Wege
1,747,836 A 2/1930 Meilink
2,345,792 A 4/1944 Cann
3,315,622 A 4/1967 Cornaro
3,559,594 A 2/1971 Miller
3,866,961 A 2/1975 List
D247,728 S * 4/1978 Nichols D6/559
D255,001 S * 5/1980 Quitman D6/559
4,391,204 A * 7/1983 Mitchell et al. 109/39
D274,858 S * 7/1984 Brush et al. D99/28
4,474,116 A 10/1984 Castenada
4,495,780 A 1/1985 Kaneko
D280,876 S * 10/1985 Chabanet D6/559
4,704,970 A 11/1987 Sanderson
4,953,683 A * 9/1990 Eisermann 194/235
D327,793 S * 7/1992 McGrory D6/448
5,160,357 A 11/1992 Faber


(57) **CLAIM**

The ornamental design for a safe, as shown and described.

DESCRIPTION

FIG. 1 shows a perspective view of a safe, according to the present invention;
FIG. 2 shows a front view of the safe of FIG. 1, illustrating the safe door with a drop slot above an eraser board on the safe door;
FIG. 3 shows a first side view of the safe of FIG. 1, illustrating a recharging port hole and door hinges;
FIG. 4 shows a second side view of the safe of FIG. 1;
FIG. 5 shows a top view of the safe of FIG. 1;
FIG. 6 shows a bottom view of the safe of FIG. 1; and,
FIG. 7 is a rear view of the safe of FIG. 1 illustrating the plate with holes for attaching the safe to a supporting surface.

1 Claim, 4 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7