

US00D518394S

(12) **United States Design Patent**
Lipscomb et al.

(10) **Patent No.:** **US D518,394 S**

(45) **Date of Patent:** **** Apr. 4, 2006**

(54) **VEHICLE DIAGNOSTIC DEVICE**

(75) Inventors: **Edward Lipscomb**, Lakeville, MN (US); **Durval Ribeiro**, Owatonna, MN (US); **Manokar Chinnadurai**, Owatonna, MN (US); **Troy Liebl**, Owatonna, MN (US)

(73) Assignee: **SPX Corporation**, Charlotte, NC (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/221,141**

(22) Filed: **Jan. 13, 2005**

(51) **LOC (8) Cl.** **10-04**

(52) **U.S. Cl.** **D10/78**

(58) **Field of Classification Search** D10/78;
324/76.12; 340/439; 701/24, 29, 35; 702/57
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | | |
|--------------|---|---------|-------------------|-------|---------|
| D242,722 S | * | 12/1976 | Bell | | D10/78 |
| D366,220 S | * | 1/1996 | Sakamoto | | D10/78 |
| D366,432 S | * | 1/1996 | Wrisley et al. | | D10/78 |
| D367,234 S | * | 2/1996 | Henney et al. | | D10/78 |
| 5,659,680 A | * | 8/1997 | Cunningham et al. | | 714/25 |
| 5,859,628 A | * | 1/1999 | Ross et al. | | 340/990 |
| 6,094,609 A | * | 7/2000 | Arjomand | | 701/29 |
| D444,085 S | * | 6/2001 | Wrisley et al. | | D10/78 |
| 6,287,519 B1 | * | 9/2001 | Nordman et al. | | 422/94 |
| 6,693,367 B1 | * | 2/2004 | Schmeisser et al. | | 701/29 |
| 6,816,760 B1 | * | 11/2004 | Namaky | | 701/29 |

* cited by examiner

Primary Examiner—Antoine D. Davis

(74) *Attorney, Agent, or Firm*—Baker & Hostetler LLP

(57) **CLAIM**

The ornamental design for a vehicle diagnostic device, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the vehicle diagnostic device; FIG. 2 is a front elevational view thereof; FIG. 3 is a rear elevational view thereof; FIG. 4 is a left side elevational view thereof; FIG. 5 is a right side elevational view thereof; FIG. 6 is a top plan view thereof; FIG. 7 is a bottom plan view thereof; FIG. 8 is a perspective view of the vehicle diagnostic device with the carrying/support strap omitted; FIG. 9 is a perspective view of a second embodiment of the vehicle diagnostic device; FIG. 10 is a front elevational view of the second embodiment; FIG. 11 is a rear elevational view of the second embodiment; and, FIG. 12 is a perspective view of the second embodiment with the carrying/support strap omitted.

The broken lines in FIGS. 1–6 and 8–12 showing the indices, button configuration, screw locations, and communication connectors are for illustrative purposes only and form no part of the claimed design.

1 Claim, 12 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

