



US00D519403S

(12) **United States Design Patent**
Berke et al.

(10) **Patent No.:** **US D519,403 S**

(45) **Date of Patent:** **** Apr. 25, 2006**

(54) **TWO PIECE SEAT BELT SHIELD**
(75) Inventors: **Joseph J. Berke**, 3248 Interlaken, W.
Bloomfield, MI (US) 48323; **James W.**
Grey, Ortonville, MI (US)

(73) Assignee: **Joseph J. Berke**, West Bloomfield, MI
(US)

(**) Term: **14 Years**

(21) Appl. No.: **29/228,501**

(22) Filed: **Apr. 25, 2005**

(51) **LOC (8) Cl.** **02-07**

(52) **U.S. Cl.** **D11/200; D2/639**

(58) **Field of Classification Search** D11/200,
D11/201, 212, 218; D2/639; 2/460, 461;
297/482; 280/808

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | | | |
|-----------|---|---|---------|------------------|-------|---------|
| 4,741,574 | A | * | 5/1988 | Weightman et al. | | 297/482 |
| D300,581 | S | * | 4/1989 | Berger et al. | | D2/635 |
| 4,838,378 | A | * | 6/1989 | Copes | | 280/808 |
| D308,287 | S | * | 6/1990 | Miller et al. | | D2/639 |
| D312,921 | S | * | 12/1990 | Chang | | D2/639 |
| D317,829 | S | * | 7/1991 | Willett et al. | | D2/639 |
| D335,472 | S | * | 5/1993 | Ward | | D11/201 |
| D337,075 | S | * | 7/1993 | Powell | | D11/200 |
| D338,552 | S | * | 8/1993 | Carrico et al. | | D2/639 |
| D341,712 | S | * | 11/1993 | Fulcher | | D2/639 |
| D343,284 | S | * | 1/1994 | Jaramillo | | D2/639 |
| 5,322,349 | A | * | 6/1994 | Gianino | | 297/482 |

| | | | | | | |
|----------|---|---|---------|----------------|-------|--------|
| D365,912 | S | * | 1/1996 | Fulcher et al. | | D2/639 |
| D369,671 | S | * | 5/1996 | Gordon | | D2/639 |
| D387,187 | S | * | 12/1997 | Connor et al. | | D2/639 |
| D387,887 | S | * | 12/1997 | Jensen | | D2/639 |
| D442,351 | S | * | 5/2001 | Moxey, Jr. | | D2/639 |
| D475,176 | S | * | 6/2003 | Moxey, Jr. | | D2/639 |

* cited by examiner

Primary Examiner—Ralf Seifert

(74) *Attorney, Agent, or Firm*—Alex Rhodes

(57) **CLAIM**

The ornamental design for a two piece seat belt shield, as shown and described.

DESCRIPTION

FIG. 1 is a top front perspective view of a two piece seat belt shield showing my new design with the attaching straps in an open position;

FIG. 2 is a bottom front perspective view of FIG. 1;

FIG. 3 is a top and front perspective view shown with the attaching straps in the attached position;


FIG. 4 is a bottom front perspective view of FIG. 3;

FIG. 5 is an exploded top perspective view shown with the straps in an unattached position. It being understood that the single line showing of broken lines are intended to be stitching; and,

FIG. 6 is a top rear perspective view shown in a position of use.

It being understood that the broken lines in FIGS. 3 and 6 are for illustrative purposes only and form no part of the claimed design.

1 Claim, 1 Drawing Sheet









FIG. 1

FIG. 2

FIG. 4

FIG. 3

FIG. 5

FIG. 6