

US00D519702S

(12) **United States Design Patent** (10) **Patent No.:** **US D519,702 S**
Boxhorn (45) **Date of Patent:** **** Apr. 25, 2006**

(54) **RELOCATION DEVICE**

(75) Inventor: **Dorothy Boxhorn**, Muskego, WI (US)

(73) Assignee: **DB Products, Inc.**, Muskego, WI (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/203,986**

(22) Filed: **Apr. 22, 2004**

(51) **LOC (8) Cl.** **09-09**

(52) **U.S. Cl.** **D34/10**

(58) **Field of Classification Search** D34/1,
D34/4, 5, 6, 7, 8, 9, 10, 11; 248/465.1, 249,
248/218.1, 153, 107, 149, 302, 303; 280/47.19,
280/79.5; 414/462, 446
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

417,578 A	12/1889	McNeill	
1,244,680 A	10/1917	Wolfe	
1,420,546 A	6/1922	Hermelink	
1,648,243 A	* 11/1927	Ramin	248/464
2,043,304 A	* 6/1936	Pfister	248/464
2,271,901 A	* 2/1942	Smith et al.	294/26
2,605,128 A	7/1952	Schneider	
2,636,627 A	4/1953	Stoker	
2,704,165 A	3/1955	Hoover	
2,745,676 A	5/1956	Scott	
2,760,668 A	* 8/1956	Wiederspan et al.	215/395
2,851,180 A	9/1958	McCabe	
2,881,007 A	4/1959	Karwatt	
2,904,345 A	9/1959	Bradley	
2,930,561 A	3/1960	Bittle	
3,188,109 A	6/1965	Broadrick	
3,214,120 A	10/1965	McKee	
3,233,764 A	2/1966	Hinsch	
3,275,175 A	9/1966	Arnold	
3,310,318 A	3/1967	Nagel	
3,370,821 A	* 2/1968	Mingis	248/452
3,376,986 A	4/1968	Farber	
3,377,085 A	4/1968	Fralick	
3,399,903 A	9/1968	Bailey	

3,598,420 A	8/1971	Edlin	
3,830,514 A	8/1974	Green	
3,893,699 A	7/1975	Morris	
4,135,725 A	1/1979	DiRoma	
5,251,944 A	10/1993	Truitt	
D341,688 S	* 11/1993	Binkley et al.	D34/5
D342,360 S	* 12/1993	Ticknor	D34/5
5,860,659 A	1/1999	Hart	
6,033,178 A	3/2000	Cummins	
6,164,896 A	12/2000	Cummins	
D436,705 S	1/2001	Dow	
6,196,509 B1	* 3/2001	Clemens	248/302
6,203,032 B1	3/2001	Ramos	
6,698,995 B1	3/2004	Bik	
6,708,990 B1	3/2004	Saino	

* cited by examiner

Primary Examiner—Cynthia E. Ramirez

(74) *Attorney, Agent, or Firm*—Nicholas A. Kees; Godfrey & Kahn, S.C.

(57) **CLAIM**

The ornamental design of a relocation device, substantially as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a relocation device showing one embodiment of the new design;
FIG. 2 is a left side view of the relocation device of FIG. 1;
FIG. 3 is a right side view of the relocation device of FIG. 1;
FIG. 4 is a rear elevational view of the relocation device of FIG. 1;
FIG. 5 is a front elevational view of the relocation device of FIG. 1;
FIG. 6 is a top plan view of the relocation device of FIG. 1;
FIG. 7 is a bottom plan view of the relocation device of FIG. 1;
FIG. 8 is a perspective view of the relocation device of FIG. 1, shown attached to a container in phantom; and,
FIG. 9 is a perspective view of the relocation device of FIG. 1, shown attached to a container and vehicle in phantom.

1 Claim, 5 Drawing Sheets




FIG. 1





FIG. 2






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

FIG. 8




FIG. 9

