



US00D519924S

(12) **United States Design Patent**
Baker et al.

(10) **Patent No.:** **US D519,924 S**

(45) **Date of Patent:** **** May 2, 2006**

(54) **FINGERPROOF, KEYED POWER CONNECTOR**

DESCRIPTION

(75) Inventors: **Craig Baker**, Shrewsbury, MA (US);
Andre Beaupre, Barre, MA (US); **Greg Norton**, Marlboro, MA (US); **Joe Belrose**, Blackstone, MA (US)

(73) Assignee: **Anderson Power Products**, Sterling, MA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/171,277**

(22) Filed: **Nov. 20, 2002**

(51) **LOC (8) Cl.** **13-03**

(52) **U.S. Cl.** **D13/133**

(58) **Field of Classification Search** D13/133,
D13/147; 439/278, 282, 290, 291, 292, 295,
439/592, 593

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,335,931	A	*	6/1982	Kinnear	439/295
D314,942	S	*	2/1991	Sato et al.	D13/147
D322,062	S	*	12/1991	Takenouchi et al.	D13/133
D323,141	S	*	1/1992	Sueyoshi et al.	D13/133
D323,142	S	*	1/1992	Nagasaka et al.	D13/133
D324,852	S	*	3/1992	Takenouchi et al.	D13/133
5,106,320	A	*	4/1992	Kinnear	439/295
D329,222	S	*	9/1992	Nagasaka et al.	D13/133
D384,034	S	*	9/1997	Kuprewicz et al.	D13/133

* cited by examiner

Primary Examiner—Philip S. Hyder

(74) *Attorney, Agent, or Firm*—Nixon Peabody LLP


(57) **CLAIM**

The ornamental design for a fingerproof, keyed power connector, as shown and described.

FIG. 1 is a perspective view of a first embodiment of a fingerproof, keyed power connector of our design; FIG. 2 is a top view of the first embodiment of the fingerproof, keyed power connector; FIG. 3 is a bottom view of the first embodiment of the fingerproof, keyed power connector; FIG. 4 is a right side view of the first embodiment of the fingerproof, keyed power connector; FIG. 5 is a left side view of the first embodiment of the fingerproof, keyed power connector; FIG. 6 is a back view of the first embodiment of the fingerproof, keyed power connector; FIG. 7 is a front view of the first embodiment of the fingerproof, keyed power connector; FIG. 8 is a front view of a second embodiment of the fingerproof, keyed power connector, the other views of the second embodiment of the fingerproof, keyed power connector are the same as the first embodiment; FIG. 9 is a front view of a third embodiment of the fingerproof, keyed power connector, the other views of the third embodiment of the fingerproof, keyed power connector are the same as the first embodiment; FIG. 10 is a front view of a fourth embodiment of the fingerproof, keyed power connector, the other views of the fourth embodiment of the fingerproof, keyed power connector are the same as the first embodiment; FIG. 11 is a front view of a fifth embodiment of the fingerproof, keyed power connector, the other views of the fifth embodiment of the fingerproof, keyed power connector are the same as the first embodiment; and, FIG. 12 is a front view of a sixth embodiment of the fingerproof, keyed power connector, the other views of the sixth embodiment of the fingerproof, keyed power connector are the same as the first embodiment.

The designations of the views as top, bottom, right side, left side, front, and back, are for ease of discussion only and are not intended to limit the design to one particular orientation. The fingerproof, keyed power connector can be oriented in other directions that would alter these designations.

1 Claim, 8 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12