



US00D520028S

(12) **United States Design Patent**  
**Simmen**

(10) **Patent No.:** **US D520,028 S**  
(45) **Date of Patent:** **\*\* May 2, 2006**

(54) **YARN-HANDLING DEVICE**

(75) Inventor: **Christian Simmen**, Wattwil (CH)

(73) Assignee: **Heberlein Fibertechnology, Inc.**,  
Wattwil (CH)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/197,810**

(22) Filed: **Jan. 22, 2004**

(30) **Foreign Application Priority Data**

Aug. 22, 2003 (CH) ..... 129 999

(51) **LOC (8) Cl.** ..... **15-06**

(52) **U.S. Cl.** ..... **D15/78**

(58) **Field of Classification Search** ..... D15/66-78;  
139/452; 57/287, 204, 207, 209, 289, 293,  
57/333, 350; 264/168; 28/254, 257, 272,  
28/271, 273

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,279,164 A	*	10/1966	Breen et al.	.....	57/287
D236,907 S	*	9/1975	Saslowsky	.....	D15/78
D267,010 S	*	11/1982	Jacobsson et al.	.....	D15/78
4,507,833 A	*	4/1985	Simmen	.....	28/254
D309,315 S	*	7/1990	Maina	.....	D15/78

(Continued)

*Primary Examiner*—Mitchell Siegel

(74) *Attorney, Agent, or Firm*—Finnegan, Henderson,  
Farabow, Garrett & Dunner, LLP

(57) **CLAIM**

The ornamental design for the yarn-handling device, as shown and described.

**DESCRIPTION**

The file of this patent contains at least one photograph executed in color. Copies of this patent with color photographs will be provided by the Office upon request and payment of the necessary fee.

FIG. 1 is a left-perspective view of a first embodiment of a yarn-handling device showing my new design;

FIG. 2 is a left perspective view of a second embodiment of my new design;

FIG. 3 is a left perspective view of a third embodiment of my new design;

FIG. 4 is a left perspective view of a fourth embodiment of my new design;

FIG. 5 is a left perspective view of a fifth embodiment of my new design;

FIG. 6 is a left perspective view of a sixth embodiment of my new design;

FIG. 7 is a left perspective view of a seventh embodiment of my new design;

FIG. 8 is a top view of the second embodiment of my new design;

FIG. 9 is a left-side view of the seventh embodiment of my new design;

FIG. 10 is a right-side view of the seventh embodiment of my new design;

FIG. 11 is a rear view of the seventh embodiment of my new design;

FIG. 12 is a front view of the seventh embodiment of my new design;

FIG. 13 is a bottom view of the seventh embodiment of my new design;

FIG. 14 is a top view of the seventh embodiment of my new design; and,

FIG. 15 is an exploded left-perspective view of the components of the seventh embodiment of my new design.

The device is comprised of two components, a base and a nozzle. The color of the base of the two component device is a part of the claimed design. The colors of the design are not limited to the exact hues, brightness, and saturations depicted.

**1 Claim, 4 Drawing Sheets**



## US D520,028 S

Page 2

---

U.S. PATENT DOCUMENTS				
D309,614 S	*	7/1990	Maina .....	D15/78
D463,463 S	*	9/2002	Zenoni et al. ....	D15/78
D464,065 S	*	10/2002	Schmodde .....	D15/78
6,651,420 B1	*	11/2003	Simmen .....	57/333
				* cited by examiner




**FIG. 1**



**FIG. 2**



**FIG. 3**



**FIG. 4**




**FIG. 5**




**FIG. 6**



**FIG. 7**




**FIG. 8**




**FIG. 9**




**FIG. 10**




**FIG. 11**




**FIG. 12**



**FIG. 13**



**FIG. 14**



**FIG. 15**