

US00D523976S

(12) **United States Design Patent** (10) **Patent No.:** **US D523,976 S**
Pfeiffer et al. (45) **Date of Patent:** **** Jun. 27, 2006**

(54) **SURFACE CONFIGURATION OF A TAILLIGHT FOR A VEHICLE**

(75) Inventors: **Peter Pfeiffer**, Boeblingen (DE);
Stephen Mattin, Sindelfingen (DE)

(73) Assignee: **DaimlerChrysler AG**, Stuttgart (DE)

(**) Term: **14 Years**

(21) Appl. No.: **29/186,974**

(22) Filed: **Jul. 25, 2003**

(51) **LOC (8) Cl.** **26-06**

(52) **U.S. Cl.** **D26/28**

(58) **Field of Classification Search** D26/28-36;
362/61, 80, 81, 82, 83, 83.3, 267, 269, 275,
362/330-340, 459-468, 475-478, 485-487
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D465,039 S	*	10/2002	Murkett	D26/28
D467,364 S	*	12/2002	Yang	D26/28
D485,920 S	*	1/2004	Yoneyama	D26/28
D494,294 S	*	8/2004	Pfeiffer	D26/28
D498,013 S	*	11/2004	Pfeiffer	D26/28
D502,274 S	*	2/2005	Abe	D26/28
D502,561 S	*	3/2005	Metros et al.	D26/28

* cited by examiner

Primary Examiner—Marcus A. Jackson

(74) *Attorney, Agent, or Firm*—Crowell & Moring LLP

(57) **CLAIM**

The ornamental design for a surface configuration of a taillight for a vehicle, as shown and described.

DESCRIPTION

This application is related to the following co-pending application, of the inventors, filed on even date herewith:

Application Serial No. 29/186,972, entitled “Surface Configuration of a Vehicle, Toy and/or Other Replicas”.

FIG. 1 is a perspective view of a first embodiment of a surface configuration of a taillight for a vehicle according to our novel design;

FIG. 2 is a front view of the first embodiment of the surface configuration of a taillight for a vehicle according to our novel design;

FIG. 3 is a perspective view of a second embodiment of the surface configuration of a taillight for a vehicle according to our novel design;

FIG. 4 is a front view of the second embodiment of the surface configuration of a taillight for a vehicle according to our novel design;

FIG. 5 is side view of the first embodiment of the surface configuration of a taillight for a vehicle according to our novel design;

FIG. 6 is a side view of the second embodiment of the surface configuration of a taillight for a vehicle according to our novel design;

FIG. 7 is a perspective view of a third embodiment of the surface configuration of a taillight for a vehicle according to our novel design;

FIG. 8 is a front view of the third embodiment of the surface configuration of a taillight for a vehicle according to our novel design;

FIG. 9 is a perspective view of a fourth embodiment of the surface configuration of a taillight for a vehicle according to our novel design;


FIG. 10 is a front view of the fourth embodiment of the surface configuration of a taillight for a vehicle according to our novel design;

FIG. 11 is a side view of the third embodiment of the surface configuration of a taillight for a vehicle according to our novel design; and,

FIG. 12 is a side view of the fourth embodiment of the surface configuration of a taillight for a vehicle according to our novel design.

The broken lines are for illustrative purposes only and form no part of the claimed design.

1 Claim, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12