

US00D524373S

(12) United States Design Patent (10) Patent No.:

Kimura (45) Date of Patent: **

US D524,373 S

Jul. 4, 2006

(54) COATING TRANSFER DEVICE

() ()	(75) Inventor:	Shigeru	Kimura,	Saitama	(JP)
---------	-----	-------------	---------	---------	---------	------

(73) Assignee: Tombow Pencil Co., Ltd., Tokyo (JP)

(**) Term: 14 Years

(21) Appl. No.: 29/214,392

(22) Filed: Oct. 4, 2004

(30) Foreign Application Priority Data

	Apr. 5, 2004 (JP)	Ap
) LOC (8) Cl	(51)
D19/69) U.S. Cl.	(52)
ification Search D19/67,) Field of Class	(58)
8, 69, 70; 156/523, 527, 577; 206/411;	D19/6	
5, 11, 19, 25, 26, 39, 56, 77; 242/588.1,	225/6	
242/588.2, 588.3, 588.6		

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

I	0355,934	S	*	2/1995	Oga et al D19/69
I	0420,389	S	*	2/2000	Shimizu
I	0421,059	S	*	2/2000	Shimizu D19/69
I	0436,625	\mathbf{S}	*	1/2001	Katami D19/69
I	0438,250	\mathbf{S}	*	2/2001	Katami D19/69
I	0446,246	\mathbf{S}	*	8/2001	Kimura D19/69
I	0451,960	S	*	12/2001	Shimizu D19/69
I	0456,450	\mathbf{S}	*	4/2002	Kimura D19/69
I	0466,158	S	*	11/2002	Suzuki
I	0466,554	S	*	12/2002	Yonezawa et al D19/67
6	5,565,657	B1	*	5/2003	Huthmacher 118/257
I	0475,745	S	*	6/2003	Ono D19/69
I	0476,035	\mathbf{S}	*	6/2003	Katami D19/69
6	5,601,632	B1	*	8/2003	Bouveresse et al 156/577
I	0489,093	\mathbf{S}	*	4/2004	Ono D19/69
I	0494,221	S	*	8/2004	Suzuki
I	0498,498	S	*	11/2004	Ono D19/69
2002	/0062928	A 1	*	5/2002	Ishikawa 156/523
2005	0155717	A 1	*	7/2005	Mitsui et al 156/77

* cited by examiner

Primary Examiner—Elizabeth A. Albert

(74) Attorney, Agent, or Firm—Birch Stewart Kolasch & Birch LLP

(57) CLAIM

The ornamental design for a coating transfer device, as shown and described.

DESCRIPTION

The coating transfer device is used for adhesive or correction tape and has a transparent casing indicated by dotted lines alternating with solid lines in the drawings. A non-transparent transfer head protrudes from the casing.

FIG. 1 is a front view of a coating transfer device with the transfer head exposed;

FIG. 2 is a rear view of the coating transfer device with the transfer head exposed;

FIG. 3 is a left side view of the coating transfer device with the transfer head exposed;

FIG. 4 is a right side view of the coating transfer device with the transfer head exposed;

FIG. 5 is a top view of the coating transfer device with the transfer head exposed;

FIG. 6 is a bottom view of the coating transfer device with the transfer head exposed;

FIG. 7 is a perspective view of the coating transfer device with the transfer head exposed;

FIG. 8 is a front view of a coating transfer device with the transfer head covered by the cap;

FIG. 9 is a rear view of the coating transfer device with the transfer head covered by the cap;

FIG. 10 is a left side view of the coating transfer device with transfer head covered by the cap;

FIG. 11 is a right side view of the coating transfer device with the transfer head covered by the cap;

FIG. 12 is a top view of the coating transfer device with the transfer head covered by the cap;

FIG. 13 is a bottom view of the coating transfer device with the transfer head covered by the cap; and,

FIG. 14 is a perspective view of the coating transfer device with the transfer head covered by the cap.

The claim is directed to the design shown in FIGS. 8–14; the design is shown without the cap in FIGS. 1–7 to more clearly show details that are less clearly visible when covered by the cap in FIGS. 8–14.

1 Claim, 2 Drawing Sheets





