

US00D527226S

(12) **United States Design Patent**  
**Maldonado**

(10) **Patent No.:** **US D527,226 S**

(45) **Date of Patent:** **\*\* Aug. 29, 2006**

(54) **SOFTSIDE COOLER**

(75) Inventor: **John Maldonado**, Katy, TX (US)

(73) Assignee: **Igloo Products Corp.**, Houston, TX (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/207,768**

(22) Filed: **Jun. 17, 2004**

(51) **LOC (8) Cl.** ..... **07-01**

(52) **U.S. Cl.** ..... **D7/607**

(58) **Field of Classification Search** ..... D7/605–608,  
D7/709, 710; D3/273, 276, 283–287, 289;  
220/915.2, 592.2, 592.24, 592.25, 915.1;  
62/457.1–457.7, 371, 372; 383/97, 110, 113  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

|           |    |   |         |               |       |          |
|-----------|----|---|---------|---------------|-------|----------|
| 2,960,136 | A  | * | 11/1960 | Ziff          | ..... | 383/110  |
| 3,139,179 | A  | * | 6/1964  | Cadotte       | ..... | 206/549  |
| D359,200  | S  | * | 6/1995  | Gowin         | ..... | D7/606   |
| D412,269  | S  | * | 7/1999  | Wyant         | ..... | D7/709   |
| D414,379  | S  | * | 9/1999  | Haberkorn     | ..... | D7/607   |
| D431,755  | S  | * | 10/2000 | Worley et al. | ..... | D7/607   |
| 6,234,677 | B1 |   | 5/2001  | Mogil         | ..... | 383/110  |
| 6,238,091 | B1 |   | 5/2001  | Mogil         | ..... | 383/110  |
| 6,247,328 | B1 |   | 6/2001  | Mogil         | ..... | 62/457.2 |
| 6,644,063 | B1 |   | 11/2003 | Mogil         | ..... | 62/457.2 |

**OTHER PUBLICATIONS**

“Igloo Times—Updating a Timeless Concept”, 2003 Product Catalog, © 2002 Igloo Products Corp.

\* cited by examiner

*Primary Examiner*—Terry A. Wallace

(74) *Attorney, Agent, or Firm*—Howrey LLP

(57) **CLAIM**

The ornamental design for a softside cooler, as shown and described.

**DESCRIPTION**

FIG. 1 is a front and right side perspective view of the softside cooler of an embodiment of the present invention, illustrating the softside cooler in a closed position;

FIG. 2 shows a front view of the softside cooler of FIG. 1 in a closed position;

FIG. 3 shows a back view of the softside cooler in a closed position;

FIG. 4 shows a right side view of the softside cooler of FIG. 1 in a closed position;


FIG. 5 shows a left side view of the softside cooler of FIG. 1 in a closed position;

FIG. 6 shows a top view of the softside cooler of FIG. 1 in a closed position;

FIG. 7 shows a bottom view of the softside cooler of FIG. 1 in a closed position; and,

FIG. 8 is a front and right side perspective view of an embodiment of the softside cooler of FIG. 1 of the present invention, illustrating the softside cooler in an open position.

**1 Claim, 4 Drawing Sheets**






Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7






Figure 8