

US00D528499S

(12) **United States Design Patent** (10) **Patent No.:** **US D528,499 S**
Creech et al. (45) **Date of Patent:** **** Sep. 19, 2006**

(54) **TIRE TREAD**

(75) Inventors: **Dean B Creech**, Easley, SC (US);
Philip B. Webb, Greenville, SC (US);
Mark Collett, Taylors, SC (US); **Luz**
M. Restrepo, Taylors, SC (US)

(73) Assignee: **Michelin Recherche et Technique**.
S.A. (CH)

(**) Term: **14 Years**

(21) Appl. No.: **29/231,177**

(22) Filed: **Jun. 2, 2005**

(51) **LOC (8) Cl.** **12-15**

(52) **U.S. Cl.** **D12/551**

(58) **Field of Classification Search** D12/544,
D12/549, 550, 551, 553, 554, 555, 556, 557,
D12/563; 152/209.1, 209.12, 209.28
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D330,882 S	11/1992	Hasegawa		D12/147
D446,170 S	8/2001	Williams		D12/146
D451,866 S	* 12/2001	Ratliff et al.		D12/551
D456,764 S	5/2002	Heinen et al.		D12/551
D459,292 S	6/2002	Hoover et al.		D12/554
D472,515 S	4/2003	Hutz et al.		D12/551
D485,228 S	* 1/2004	Hutz et al.		D12/551
6,983,777 B1	* 1/2006	Ratliff, Jr.		152/209.15

OTHER PUBLICATIONS

BFGoodrich g-Force T/A KDW Tire, 2004 Tread Design
Guide, Jan. 2004, p. 11. 1/1.*
Mastercraft Avenger 4x4 Tire, 2004 Tread Design Guide,
Jan. 2004, p. 38. 4/1.*

Tread design Guide, 1992, p. 41, BGGoodrich COMP T/A
ZR.

Tread design Guide, 1999, p. 13, Barum OR58 Bravura.

Tread Design Guide, 1999, p. 72, Toyo Proxes U1.

Tread Design Guide, 2002, p. 46, Medalist Defender ZR.

Tread Design Guide, 2002, p. 54, Nitto NT-450 Extreme.

Tread Design Guide, 2002, p. 59, Riken Defender HR.

Tread Design Guide, 2002, p. 65, Summit Pacemark Super
GT HR.

* cited by examiner

Primary Examiner—Robert M. Spear

(74) *Attorney, Agent, or Firm*—E. Martin Remick; Adam
Arnold

(57) **CLAIM**

The ornamental design for a tire tread, as shown and
described.


DESCRIPTION

FIG. 1 is a perspective view of a tire tread of this invention
showing our new design, it being understood that the tread
pattern repeats circumferentially throughout the outer cir-
cumference and shoulder of a tire, the opposite side per-
spective view being an inverted image thereto; and,

FIG. 2 is an enlarged fragmentary front elevation view of the
tire tread thereof of FIG. 1.

In the drawings, the dark stippled surface shading represents
the recessed groove portions of the tire tread having a depth
as best illustrated along the right edge of FIG. 1. The broken
line disclosure of the tire sidewall and inner bead is for
illustrative purposes only and forms no part of the claimed
design.

1 Claim, 2 Drawing Sheets






Fig. 1




Fig. 2