US00D530265S

(12) United States Design Patent

Hutz et al.

(10) Patent No.: US D530,265 S
(45) Date of Patent: ** Oct. 17, 2006

(54) **TIRE TREAD**

(75) Inventors: **John Anthony Hutz**, Greer, SC (US); **Stephen Lash**, Simpsonville, SC (US); **Gary Dean Enterline**, Greer, SC (US)

(73) Assignee: **Michelin Recherche et Technique S.A.**, Granges-Paccot (CH)

(**) Term: **14 Years**

(21) Appl. No.: **29/238,518**

(22) Filed: **Sep. 16, 2005**

(51) **LOC (8) Cl.** **12-15**

(52) **U.S. Cl.** **D12/579**

(58) **Field of Classification Search** D12/511, D12/512, 513, 543, 544, 545, 565, 578, 579, D12/580, 600, 601, 901; 152/209.1, 209.8, 152/209.12, 209.18, 209.28
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D112,993	S	*	1/1939	Hardeman	D12/571
3,559,712	A	*	2/1971	Verdier	152/209.14
D295,617	S	*	5/1988	Sedlack	D12/579
D385,520	S	*	10/1997	Scheuren et al.	D12/602
D393,236	S		4/1998	Rowe	D12/147
D402,239	S		12/1998	Le et al.	D12/146
D430,833	S	*	9/2000	Allison	D12/579
D447,447	S		9/2001	Guspodin et al.	D12/147
D453,310	S		2/2002	Allison et al.	D12/147
D483,718	S		12/2003	Hutz et al.	D12/579
D500,285	S		12/2004	Ikeda	D12/579
D512,370	S	*	12/2005	Pang	D12/579

OTHER PUBLICATIONS

Bridgestone VLTS V–Steel L–Traction S Tire, 2004 Tread Design Guide, Jan. 2004, p. 153. 1/1.*
Tread Design Guide, 1997, pp. 181, Toyo T–451.
Tread Design Guide, 1998, pp. 145, Kelly–Springfield Armorsteel KTM 1.
Tread Design Guide, 2001, pp. 157, Bridgestone VLS V–Steel L–Traction S.
Tread Design Guide, 2001, pp. 166, Michelin XADN.

* cited by examiner

Primary Examiner—Robert M. Spear
(74) *Attorney, Agent, or Firm*—E. Martin Remick; Adam Arnold

(57) **CLAIM**

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. **1** is a perspective view of a tire tread of this invention showing our new design, it being understood that the tread pattern repeats circumferentially throughout the outer circumference and shoulder of a tire, the opposite side perspective view being identical thereto; and,
FIG. **2** is an enlarged fragmentary front elevation view of the tire tread thereof of FIG. **1**.
In the drawings, the dark stippled surface shading represents the recessed groove portions of the tire tread having a depth as best illustrated along the right edge of FIG. **1**. The broken line disclosure of the tire sidewall and inner bead is for illustrative purposes only and forms no part of the claimed design.

1 Claim, 2 Drawing Sheets





Fig. 1



Fig. 2