



US00D530635S

(12) **United States Design Patent**
Bosch

(10) **Patent No.:** **US D530,635 S**

(45) **Date of Patent:** **** Oct. 24, 2006**

(54) **SENSOR**

5,784,282 A * 7/1998 Abitbol et al. 700/186
5,790,242 A * 8/1998 Stern et al. 356/4.04
6,930,763 B1 * 8/2005 Harding 356/3.1

(75) Inventor: **Antonio Ventura-Traveset Bosch**, Las Arenas (ES)

* cited by examiner

(73) Assignee: **Datapixel, S.L.** (ES)

Primary Examiner—Antoine D. Davis

(**) Term: **14 Years**

(74) *Attorney, Agent, or Firm*—Ostrolenk, Faber, Gerb & Soffen, LLP

(21) Appl. No.: **29/234,979**

(57) **CLAIM**

(22) Filed: **Jul. 26, 2005**

The ornamental design for a sensor, as shown and described.

(30) **Foreign Application Priority Data**

DESCRIPTION

Jan. 27, 2005 (EM) 000286091

(51) **LOC (8) Cl.** **10-04**

FIG. 1 is a front right side perspective view of the sensor of the present invention;

(52) **U.S. Cl.** **D10/70**

FIG. 2 is a right side view thereof;

(58) **Field of Classification Search** D10/70,

FIG. 3 is a front view thereof;

D10/46; 356/3.1, 4.04, 4.05, 4.06; 700/192,
700/259; 901/47

FIG. 4 is a top view thereof;

See application file for complete search history.

FIG. 5 is a left side view thereof;

(56) **References Cited**


FIG. 6 is a rear view thereof; and,

U.S. PATENT DOCUMENTS

FIG. 7 is a bottom view thereof.

4,879,664 A * 11/1989 Suyama et al. 700/186

1 Claim, 7 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7