

US00D534448S

(12) **United States Design Patent**
Shaffer, II et al.

(10) **Patent No.: US D534,448 S**
(45) **Date of Patent: ** Jan. 2, 2007**

(54) **AUTHENTICATION DEVICE**

(75) Inventors: **Robert W. Shaffer, II**, East Templeton,
MA (US); **Edward W. Vipond**,
Leominster, MA (US)

(73) Assignee: **RSA Security Inc.**, Bedford, MA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/243,882**

(22) Filed: **Nov. 30, 2005**

(51) **LOC (8) Cl.** **10-05**

(52) **U.S. Cl.** **D10/104; D10/106**

(58) **Field of Classification Search** D10/104,
D10/106; 340/571, 572.7–572.9, 573.4, 572.1–572.8,
340/686.6, 568.2–568.8, 539; 70/57.1; 24/704.1
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D415,441 S * 10/1999 Pinchuk D10/104
D493,739 S * 8/2004 Copen D10/104
2002/0158762 A1 * 10/2002 Nguyen et al. 340/572.9
2004/0239505 A1 * 12/2004 Hogan et al. 340/572.9
2005/0001726 A1 * 1/2005 Valade et al. 340/572.9

* cited by examiner

Primary Examiner—Antoine D. Davis

(74) *Attorney, Agent, or Firm*—Wilmer Cutler Pickering
Hale and Dorr LLP

(57) **CLAIM**


The ornamental design for authentication device, as shown
and described.

DESCRIPTION

FIG. 1 is a top perspective view of one embodiment of a
security device showing our new design;
FIG. 2 is a bottom perspective view thereof;
FIG. 3 is a front view thereof;

FIG. 4 is a back view thereof;
FIG. 5 is a bottom view thereof;
FIG. 6 is a side view thereof;
FIG. 7 is a top view thereof;
FIG. 8 is a side view thereof;
FIG. 9 is a top perspective view of the authentication device
shown in FIG. 1 with the connector component shown
partially rotated within the case for completeness of illus-
tration;
FIG. 10 is a bottom perspective view of the security device
shown in FIG. 9;
FIG. 11 is a front view thereof;
FIG. 12 is a back view thereof;
FIG. 13 is a side view thereof;
FIG. 14 is a bottom view thereof;
FIG. 15 is a side view thereof; and,
FIG. 16 is a top view thereof;
FIG. 17 is a top perspective view of the authentication
device shown in FIG. 1 with the connector component
shown completely rotated within the case and unlocked for
completeness of illustration;
FIG. 18 is a bottom perspective view of the security device
shown in FIG. 17;
FIG. 19 is a front view thereof;
FIG. 20 is a back view thereof;
FIG. 21 is a side view thereof;
FIG. 22 is a top view thereof;
FIG. 23 is a side view thereof; and,
FIG. 24 is a bottom view thereof;
FIG. 25 is a top perspective view of the authentication
device shown in FIG. 1 with the connector component
shown completely rotated within the case and locked for
completeness of illustration;
FIG. 26 is a bottom perspective view of the security device
shown in FIG. 25;
FIG. 27 is a front view thereof;
FIG. 28 is a back view thereof;
FIG. 29 is a side view thereof;
FIG. 30 is a top view thereof;
FIG. 31 is a side view thereof; and,
FIG. 32 is a bottom view thereof.

1 Claim, 9 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 8




FIG. 7




FIG. 6




FIG. 5

FIG. 9




FIG. 10




FIG. 11





FIG. 12






FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32